

---

Subject: Re: Root Server - IPtables

Posted by [Vasily Tarasov](#) on Mon, 26 Feb 2007 17:14:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Well, everything is .explainable now.

According to your rules:

Chain INPUT (policy ACCEPT 0 packets, 0 bytes)  
pkts bytes target prot opt in out source destination  
62 4986 RH-Firewall-1-INPUT all -- \* \* 0.0.0.0/0 0. 0.0.0/0

Chain FORWARD (policy ACCEPT 0 packets, 0 bytes)  
pkts bytes target prot opt in out source destination  
324 59500 RH-Firewall-1-INPUT all -- \* \* 0.0.0.0/0 0. 0.0.0/0

Chain OUTPUT (policy ACCEPT 354 packets, 46842 bytes)  
pkts bytes target prot opt in out source destination

Chain RH-Firewall-1-INPUT (2 references)  
pkts bytes target prot opt in out source destination  
0 0 ACCEPT all -- lo \* 0.0.0.0/0 0.0.0.0/0  
0 0 ACCEPT icmp -- \* \* 0.0.0.0/0 0.0.0.0/0 icmp type 255  
0 0 ACCEPT esp -- \* \* 0.0.0.0/0 0.0.0.0/0  
0 0 ACCEPT ah -- \* \* 0.0.0.0/0 0.0.0.0/0  
0 0 ACCEPT udp -- \* \* 0.0.0.0/0 224.0.0.251 udp dpt:5353  
0 0 ACCEPT udp -- \* \* 0.0.0.0/0 0.0.0.0/0 udp dpt:631  
47 3544 ACCEPT all -- \* \* 0.0.0.0/0 0.0.0.0/0 state RELATED,ESTABLISHED  
0 0 ACCEPT tcp -- \* \* 0.0.0.0/0 0.0.0.0/0 state NEW tcp dpt:22  
339 60942 REJECT all -- \* \* 0.0.0.0/0 0.0.0.0/0 reject-with icmp-host-prohibited

VE traffic is prohibited. Just read more carefully iptables manual.

Vasily

---