
Posted by [weldpua2008](#) on Mon, 12 Mar 2007 22:15:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
/sbin/ifconfig eth1 0
/sbin/ifconfig eth1 up
vzctl set 222 --netif_add eth1,00:12:34:56:78:9A,veth101.0,00:12:34:56:78:9B --save
vzctl start 222
/sbin/ifconfig veth101.0 0
/bin/echo 1 > /proc/sys/net/ipv4/conf/veth101.0/forwarding
/bin/echo 1 > /proc/sys/net/ipv4/conf/veth101.0/proxy_arp
/bin/echo 1 > /proc/sys/net/ipv4/conf/eth1/forwarding
/bin/echo 1 > /proc/sys/net/ipv4/conf/eth1/proxy_arp
```

```
/sbin/ifconfig eth1 0
/sbin/ip addr add 10.11.25.5 dev eth1
/sbin/route delete default
/sbin/ip route add default dev eth1
route add default gw 10.11.25.5
```

```
# ping 10.11.25.5
PING 10.11.25.5 (10.11.25.5): 56 data bytes
```

```
Vr HL TOS Len ID Flg off TTL Pro cks Src Dst
4 5 00 0054 63ce 0 0000 3f 01 d1bf 10.11.25.1 10.11.25.5
```