
Subject: Re: 2 interfaces on VE, each using a separate routes

Posted by [jyap](#) on Wed, 14 Mar 2007 18:41:46 GMT

[View Forum Message](#) <> [Reply to Message](#)

That works for me.

Doing more testing, when I take out the global default route on the Host (10.0.0.1) I can't ping 10.0.0.x from the VE. It's as if the VE inherits only the global default route from the Host. However, when I take out the global default route, I am able to ping external IPs on the internet.

The VE automatically specifies its default gateway as 192.0.2.1 (through /etc/sysconfig/network). I'm not sure if that's related.

- Julian

On 3/14/07, Andrey Mirkin <amirkin@sw.ru> wrote:

> Hello,

>

> Can you, please, try to ping from VE using following command:

> ping 192.168.1.1 -I 192.168.1.9

>

> The thing is that ping takes the first IP address from interface as default.

>

> On Wednesday 14 March 2007 13:29 Julian Yap wrote:

> > Hi people.

> >

> > Firstly, thanks for OpenVZ. I really appreciate the hard work put

> > into the community aspects. Very impressed to see how far OpenVZ has

> > come since it's launch.

> >

> > I have a VE that I've added 2 IP's to. Both on different networks.

> > This was by using the default --ipadd option of vzctl.

> > eg.

> > 10.0.0.9

> > 192.168.1.9

> >

> > On the Host I have set up Source based routing according to the

> > example on the page:

> > <http://gflug.net/~mdmartz/index.php/Linux:Network:DualNetRouteHack>

> > eg.

> > eth0 - 10.0.0.5 - Default route --> 10.0.0.1

> > eth1 - 192.168.1.5 - Default route --> 191.168.1.1

> >

> > On the Host, I am able to ping both default routes. On the VE, I can

> > only ping the first default gateway, 10.0.0.1. I'm unable to ping

> > 192.168.1.1.

> >

> > Is it possible to have 2 interfaces on a VE, each using a separate
> > route? Feel free to just outline the general concept of what I have
> > to do :). Any help would be greatly appreciated.

> >

> > Thanks,

> >

> > Julian
