
Subject: [PATCH RESEND 2/2] Fix some kallsyms_lookup() vs rmmod races
Posted by [Alexey Dobriyan](#) on Fri, 16 Mar 2007 11:39:01 GMT
[View Forum Message](#) <> [Reply to Message](#)

[cc'ing folks whose proc files are affected]

kallsyms_lookup() can call module_address_lookup() which iterates over modules list without module_mutex taken. Comment at the top of module_address_lookup() says it's for oops resolution so races are irrelevant, but in some cases it's reachable from regular code:

BUG: unable to handle kernel paging request at virtual address f94fb19c
printing eip:
c0138097
*pde = 33576067
Oops: 0000 [#1]
PREEMPT
Modules linked in: ohci_hcd af_packet e1000 ehci_hcd uhci_hcd usbcore
CPU: 0
EIP: 0060:[<c0138097>] Not tainted VLI
EFLAGS: 00010246 (2.6.21-rc3-8b9909ded6922c33c221b105b26917780cfa497d #25)
EIP is at module_address_lookup+0x43/0x24c
eax: 00000000 ebx: 00000000 ecx: f94fb080 edx: f882e704
esi: 00000000 edi: 00000000 ebp: 00000000 esp: d30b8e78
ds: 007b es: 007b fs: 00d8 gs: 0033 ss: 0068
Process cat (pid: 13274, ti=d30b8000 task=d2b50af0 task.ti=d30b8000)
Stack: d30b8f44 d30b8f48 00008001 00000000 c039a23c d30b8ec4 00000000 d30b8f44
d30b8f48 c013876c d30b8f4c 00000000 cf544000 ffffffff d38ebb7c c01880ff
d30b8f4c d30b8ec4 00000246 c0399600 00000001 00000001 00000000 c0399654
Call Trace:
[<c013876c>] kallsyms_lookup+0x5e/0x7c
[<c01880ff>] proc_pid_wchan+0x38/0x76
[<c01404fe>] __alloc_pages+0x4f/0x2f9
[<c01891c6>] proc_info_read+0x6f/0xa8
[<c015bbfd>] sys_fstat64+0x1e/0x23
[<c01592d4>] vfs_read+0x7d/0xb5
[<c0189157>] proc_info_read+0x0/0xa8
[<c0159621>] sys_read+0x41/0x6a
[<c0103e72>] sysenter_past_esp+0x5f/0x99
=====

Code: 04 8b 51 04 0f 18 02 90 81 3d 4c 8d 39 c0 4c 8d 39 c0 74 3f 8b b9 18 01 00 00 8b 99 10
01 00 00 39 eb 77 07 8d 04 3b 39 c5 72 32 <8b> b1 1c 01 00 00 8b 81 14 01 00 00 39 c5 72 06
01 f0 39 c5 72
EIP: [<c0138097>] module_address_lookup+0x43/0x24c SS:ESP 0068:d30b8e78

Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>

```

fs/proc/base.c      | 7 ++++++
kernel/time/timer_list.c | 6 ++++++
kernel/time/timer_stats.c | 6 ++++++
mm/slab.c           | 3 +++
4 files changed, 22 insertions(+)

```

```

--- a/fs/proc/base.c
+++ b/fs/proc/base.c
@@ -61,6 +61,7 @@ #include <linux/seq_file.h>
#include <linux/namei.h>
#include <linux/mnt_namespace.h>
#include <linux/mm.h>
+#include <linux/module.h>
#include <linux/smp_lock.h>
#include <linux/rcupdate.h>
#include <linux/kallsyms.h>
@@ -282,7 +283,13 @@ static int proc_pid_wchan(struct task_st

    wchan = get_wchan(task);

+ module_mutex_lock();
+ sym_name = kallsyms_lookup(wchan, &size, &offset, &modname, namebuf);
+ /*
+  * size, offset, modname aren't used, sym_name is copied into namebuf,
+  * so drop it now.
+  */
+ module_mutex_unlock();
+ if (sym_name)
+     return sprintf(buffer, "%s", sym_name);
+     return sprintf(buffer, "%lu", wchan);
--- a/kernel/time/timer_list.c
+++ b/kernel/time/timer_list.c
@@ -44,7 +44,13 @@ static void print_name_offset(struct seq
const char *sym_name;
char *modname;

+ module_mutex_lock();
+ sym_name = kallsyms_lookup(addr, &size, &offset, &modname, namebuf);
+ /*
+  * size, offset, modname aren't used, sym_name is copied into namebuf,
+  * so drop it now.
+  */
+ module_mutex_unlock();
+ if (sym_name)
+     SEQ_printf(m, "%s", sym_name);
+     else
--- a/kernel/time/timer_stats.c
+++ b/kernel/time/timer_stats.c

```

```

@@ -262,7 +262,13 @@ static void print_name_offset(struct seq
    const char *sym_name;
    char *modname;

+ module_mutex_lock();
    sym_name = kallsyms_lookup(addr, &size, &offset, &modname, namebuf);
+ /*
+  * size, offset, modname aren't used, sym_name is copied into namebuf,
+  * so drop it now.
+  */
+ module_mutex_unlock();
    if (sym_name)
        seq_printf(m, "%s", sym_name);
    else
--- a/mm/slab.c
+++ b/mm/slab.c
@@ -4385,14 +4385,17 @@ #ifdef CONFIG_KALLSYMS
    unsigned long offset, size;
    char namebuf[KSYM_NAME_LEN+1];

+ module_mutex_lock();
    name = kallsyms_lookup(address, &size, &offset, &modname, namebuf);

    if (name) {
        seq_printf(m, "%s+ %#lx/%#lx", name, offset, size);
        if (modname)
            seq_printf(m, " [%s]", modname);
+ module_mutex_unlock();
        return;
    }
+ module_mutex_unlock();
#endif
    seq_printf(m, "%p", (void *)address);
}

```
