
Subject: Re: [PATCH] Check for error returned by kthread_create on creating journal thread

Posted by [xemul](#) on Mon, 16 Apr 2007 11:07:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

Christoph Hellwig wrote:

> On Mon, Apr 16, 2007 at 11:41:14AM +0400, Pavel Emelianov wrote:

>> If the thread failed to create the subsequent wait_event

>> will hang forever.

>>

>> This is likely to happen if kernel hits max_threads limit.

>>

>> Will be critical for virtualization systems that limit the

>> number of tasks and kernel memory usage within the container.

>

>> --- ./fs/jbd/journal.c.jbdthreads 2007-04-16 11:17:36.000000000 +0400

>> +++ ./fs/jbd/journal.c 2007-04-16 11:30:09.000000000 +0400

>> @@ -211,10 +211,16 @@ end_loop:

>> return 0;

>> }

>>

>> -static void journal_start_thread(journal_t *journal)

>> +static int journal_start_thread(journal_t *journal)

>> {

>> - kthread_run(kjournald, journal, "kjournald");

>> + struct task_struct *t;

>> +

>> + t = kthread_run(kjournald, journal, "kjournald");

>> + if (IS_ERR(t))

>> + return PTR_ERR(t);

>> +

>> wait_event(journal->j_wait_done_commit, journal->j_task != 0);

>

> Note that this wait_event should exist at all, and the return

Should NOT you mean?

> value of kthread_run should be assigned to journal->j_task. Also

> the code doesn't use the kthread primitives in other places leading

> to cruffy code.

Well, this could be done with a separate patch, I think.

> -

> To unsubscribe from this list: send the line "unsubscribe linux-kernel" in

> the body of a message to majordomo@vger.kernel.org

> More majordomo info at <http://vger.kernel.org/majordomo-info.html>

> Please read the FAQ at <http://www.tux.org/lkml/>

>
