

---

Subject: [PATCH 5/9] Containers (V9): Add container\_clone() interface

Posted by [Paul Menage](#) on Fri, 27 Apr 2007 10:46:12 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

This patch adds support for container\_clone(), a speculative interface to creating new containers intended to be used for systems such as namespace unsharing.

Signed-off-by: Paul Menage <[menage@google.com](mailto:menage@google.com)>

---

```
include/linux/container.h |  2
kernel/container.c      | 121 ++++++++++++++++++++++++++++++++++++++++
2 files changed, 123 insertions(+)
```

Index: container-2.6.21-rc7-mm1/kernel/container.c

=====

```
--- container-2.6.21-rc7-mm1.orig/kernel/container.c
+++ container-2.6.21-rc7-mm1/kernel/container.c
@@ -1619,3 +1619,124 @@ void container_exit(struct task_struct *
    tsk->containers = init_task.containers;
    task_unlock(tsk);
}
+
+static atomic_t namecnt;
+static void get_unused_name(char *buf) {
+ sprintf(buf, "node%d", atomic_inc_return(&namecnt));
+}
+
+/**
+ * container_clone - duplicate the current container in the hierarchy
+ * that the given subsystem is attached to, and move this task into
+ * the new child
+ */
+int container_clone(struct task_struct *tsk, struct container_subsys *subsys)
+{
+ struct dentry *dentry;
+ int ret = 0;
+ char nodename[32];
+ struct container *parent, *child;
+ struct inode *inode;
+ struct css_group *cg;
+ struct containerfs_root *root;
+
+ /* We shouldn't be called by an unregistered subsystem */
+ BUG_ON(!subsys->active);
+
+ /* First figure out what hierarchy and container we're dealing
```

```

+ * with, and pin them so we can drop container_mutex */
+ mutex_lock(&container_mutex);
+ again:
+ root = subsys->root;
+ if (root == &rootnode) {
+ printk(KERN_INFO
+       "Not cloning container for unused subsystem %s\n",
+       subsys->name);
+ mutex_unlock(&container_mutex);
+ return 0;
+ }
+ cg = &tsk->containers;
+ parent = task_container(tsk, subsys->subsys_id);
+ /* Pin the hierarchy */
+ atomic_inc(&parent->root->sb->s_active);
+
+ mutex_unlock(&container_mutex);
+
+ /* Now do the VFS work to create a container */
+ get_unused_name(nodename);
+ inode = parent->dentry->d_inode;
+
+ /* Hold the parent directory mutex across this operation to
+ * stop anyone else deleting the new container */
+ mutex_lock(&inode->i_mutex);
+ dentry = container_get_dentry(parent->dentry, nodename);
+ if (IS_ERR(dentry)) {
+ printk(KERN_INFO
+       "Couldn't allocate dentry for %s: %ld\n", nodename,
+       PTR_ERR(dentry));
+ ret = PTR_ERR(dentry);
+ goto out_release;
+ }
+
+ /* Create the container directory, which also creates the container */
+ ret = vfs_mkdir(inode, dentry, S_IFDIR | 0755);
+ child = __d_cont(dentry);
+ dput(dentry);
+ if (ret) {
+ printk(KERN_INFO
+       "Failed to create container %s: %d\n", nodename,
+       ret);
+ goto out_release;
+ }
+
+ if (!child) {
+ printk(KERN_INFO
+       "Couldn't find new container %s\n", nodename);

```

```

+ ret = -ENOMEM;
+ goto out_release;
+
+ /* The container now exists. Retake container_mutex and check
+ * that we're still in the same state that we thought we
+ * were. */
+ mutex_lock(&container_mutex);
+ if ((root != subsys->root) ||
+     (parent != task_container(tsk, subsys->subsys_id))) {
+ /* Aargh, we raced ... */
+ mutex_unlock(&inode->i_mutex);
+
+ deactivate_super(parent->root->sb);
+ /* The container is still accessible in the VFS, but
+ * we're not going to try to rmdir() it at this
+ * point. */
+ printk(KERN_INFO
+       "Race in container_clone() - leaking container %s\n",
+       nodename);
+ goto again;
+
+ /* All seems fine. Finish by moving the task into the new container */
+ ret = attach_task(child, tsk);
+ mutex_unlock(&container_mutex);
+
+ out_release:
+ mutex_unlock(&inode->i_mutex);
+ deactivate_super(parent->root->sb);
+ return ret;
+}
+
+/* See if "cont" is a descendant of the current task's container in
+ * the appropriate hierarchy */
+
+int container_is_descendant(const struct container *cont) {
+ int ret;
+ struct container *target;
+ int subsys_id;
+ get_first_subsys(cont, NULL, &subsys_id);
+ target = task_container(current, subsys_id);
+ while (cont != target && cont!= cont->top_container) {
+ cont = cont->parent;
+ }
+ ret = (cont == target);
+ return ret;
+}

```

Index: container-2.6.21-rc7-mm1/include/linux/container.h  
=====--- container-2.6.21-rc7-mm1.orig/include/linux/container.h  
+++ container-2.6.21-rc7-mm1/include/linux/container.h  
@@ -189,6 +189,8 @@ static inline struct container\* task\_con

```
int container_path(const struct container *cont, char *buf, int buflen);  
+int container_clone(struct task_struct *tsk, struct container_subsys *ss);  
+#else /* !CONFIG_CONTAINERS */  
static inline int container_init_early(void) { return 0; }  
  
--
```