
Subject: Re: LTP: serge2 hostname
Posted by [serue](#) on Wed, 23 May 2007 14:49:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

Quoting Alexey Dobriyan (adobriyan@sw.ru):
> I ran ltp-full-20070430 and utstest.c forgot to restore original
> hostname from serge2. ;-)

Oh that's just me taking over the world, one workstation at a time.

Hopefully this simple obvious silly workaround fixes it?

It should also fix 'make no_ltp' which I hadn't realized was broken
until I just tried to test the hostname fix...

thanks for spotting that.

-serge

```
Only in ltp-full-20070430-fixserge2/testcases/kernel/containers/libc lone: libclone.a
Only in ltp-full-20070430-fixserge2/testcases/kernel/containers/libc lone: libclone.o
diff -ur ltp-full-20070430/testcases/kernel/containers/utsname/Makefile
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/Makefile
--- ltp-full-20070430/testcases/kernel/containers/utsname/Makefile 2007-04-26
13:02:51.000000000 +0200
+++ ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/Makefile 2007-05-23
16:48:26.000000000 +0200
@@ -4,8 +4,9 @@
LDLIBS += -L../lib -L../libclone ../libclone/libclone.a -lltp

SRCS = $(wildcard *.c)
+NOLTPSRCS = utstest.c
TARGETS = $(patsubst %.c,%,$(SRCS))
-NOLTP_TARGETS = $(patsubst %.c,%_noltp,$(SRCS))
+NOLTP_TARGETS = $(patsubst %.c,%_noltp,$(NOLTPSRCS))

%_noltp : %.c
$(CC) -g -DNO_LTP -o $@ $< ../libclone/libclone.a
diff -ur ltp-full-20070430/testcases/kernel/containers/utsname/runtests_noltp.sh
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/runtests_noltp.sh
--- ltp-full-20070430/testcases/kernel/containers/utsname/runtests_noltp.sh 2007-04-26
13:02:51.000000000 +0200
+++ ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/runtests_noltp.sh 2007-05-23 16:44:32.000000000 +0200
@@ -1,5 +1,6 @@
#!/bin/sh

+oldhostname=`hostname`
```

```

exit_code=0
echo "unshare tests"
for i in `seq 1 5`; do
@@ -17,4 +18,5 @@
    exit_code=$?
fi
done
+hostname "$oldhostname"
exit $exit_code
diff -ur ltp-full-20070430/testcases/kernel/containers/utsname/runuts test.sh
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/runutstest.sh
--- ltp-full-20070430/testcases/kernel/containers/utsname/runuts test.sh 2007-04-26
13:02:51.000000000 +0200
+++ ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/runutstest.sh 2007-05-23
16:44:37.000000000 +0200
@@ -1,5 +1,6 @@
#!/bin/sh

+oldhostname=`hostname`
echo "unshare tests"
for i in `seq 1 5`; do
    echo "test $i (unshare)"
@@ -10,3 +11,4 @@
    echo "test $i (clone)"
    utstest clone $i
done
+hostname "$oldhostname"
Only in ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname: utstest_noltp

```
