
Subject: [PATCH 1/8] Resource counters

Posted by [Pavel Emelianov](#) on Wed, 30 May 2007 15:22:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

Introduce generic structures and routines for resource accounting.

Each resource accounting container is supposed to aggregate it,
container_subsystem_state and its resource-specific members within.

Signed-off-by: Pavel Emelianov <xemul@openvz.org>

```
diff -upr linux-2.6.22-rc2-mm1.orig/include/linux/res_counter.h
linux-2.6.22-rc2-mm1-0/include/linux/res_counter.h
--- linux-2.6.22-rc2-mm1.orig/include/linux/res_counter.h 2007-05-30 16:16:58.000000000 +0400
+++ linux-2.6.22-rc2-mm1-0/include/linux/res_counter.h 2007-05-30 16:13:09.000000000 +0400
@@ -0,0 +1,83 @@
+ #ifndef __RES_COUNTER_H__
+ #define __RES_COUNTER_H__
+ /*
+  * resource counters
+  *
+  * Copyright 2007 OpenVZ SWsoft Inc
+  *
+  * Author: Pavel Emelianov <xemul@openvz.org>
+  *
+  */
+ #include <linux/container.h>
+
+ struct res_counter {
+     unsigned long usage;
+     unsigned long limit;
+     unsigned long failcnt;
+     spinlock_t lock;
+ };
+
+ enum {
+     RES_USAGE,
+     RES_LIMIT,
+     RES_FAILCNT,
+ };
+
+ ssize_t res_counter_read(struct res_counter *cnt, int member,
+     const char __user *buf, size_t nbytes, loff_t *pos);
+ ssize_t res_counter_write(struct res_counter *cnt, int member,
+     const char __user *buf, size_t nbytes, loff_t *pos);
```

```

+
+static inline void res_counter_init(struct res_counter *cnt)
+{
+ spin_lock_init(&cnt->lock);
+ cnt->limit = (unsigned long)LONG_MAX;
+}
+
+static inline int res_counter_charge_locked(struct res_counter *cnt,
+ unsigned long val)
+{
+ if (cnt->usage <= cnt->limit - val) {
+ cnt->usage += val;
+ return 0;
+ }
+
+ cnt->failcnt++;
+ return -ENOMEM;
+}
+
+static inline int res_counter_charge(struct res_counter *cnt,
+ unsigned long val)
+{
+ int ret;
+ unsigned long flags;
+
+ spin_lock_irqsave(&cnt->lock, flags);
+ ret = res_counter_charge_locked(cnt, val);
+ spin_unlock_irqrestore(&cnt->lock, flags);
+ return ret;
+}
+
+static inline void res_counter_uncharge_locked(struct res_counter *cnt,
+ unsigned long val)
+{
+ if (unlikely(cnt->usage < val)) {
+ WARN_ON(1);
+ val = cnt->usage;
+ }
+
+ cnt->usage -= val;
+}
+
+static inline void res_counter_uncharge(struct res_counter *cnt,
+ unsigned long val)
+{
+ unsigned long flags;
+
+ spin_lock_irqsave(&cnt->lock, flags);

```

```

+ res_counter_uncharge_locked(cnt, val);
+ spin_unlock_irqrestore(&cnt->lock, flags);
+}
+
+
+endif
diff -upr linux-2.6.22-rc2-mm1.orig/init/Kconfig linux-2.6.22-rc2-mm1-0/init/Kconfig
--- linux-2.6.22-rc2-mm1.orig/init/Kconfig 2007-05-30 16:13:08.000000000 +0400
+++ linux-2.6.22-rc2-mm1-0/init/Kconfig 2007-05-30 16:13:09.000000000 +0400
@@ -328,6 +328,10 @@ config CPUSETS

```

Say N if unsure.

```

+config RESOURCE_COUNTERS
+ bool
+ select CONTAINERS
+
+config SYSFS_DEPRECATED
+ bool "Create deprecated sysfs files"
+ default y
diff -upr linux-2.6.22-rc2-mm1.orig/kernel/Makefile linux-2.6.22-rc2-mm1-0/kernel/Makefile
--- linux-2.6.22-rc2-mm1.orig/kernel/Makefile 2007-05-30 16:13:08.000000000 +0400
+++ linux-2.6.22-rc2-mm1-0/kernel/Makefile 2007-05-30 16:13:09.000000000 +0400
@@ -56,6 +56,7 @@ obj-$(CONFIG_SYSCTL) += utsname_sysctl.o
obj-$(CONFIG_UTS_NS) += utsname.o
obj-$(CONFIG_TASK_DELAY_ACCT) += delayacct.o
obj-$(CONFIG_TASKSTATS) += taskstats.o tsacct.o
+obj-$(CONFIG_RESOURCE_COUNTERS) += res_counter.o

```

```

ifneq ($(CONFIG_SCHED_NO_NO_OMIT_FRAME_POINTER),y)
# According to Alan Modra <alan@linuxcare.com.au>, the -fno-omit-frame-pointer is
diff -upr linux-2.6.22-rc2-mm1.orig/kernel/res_counter.c
linux-2.6.22-rc2-mm1-0/kernel/res_counter.c
--- linux-2.6.22-rc2-mm1.orig/kernel/res_counter.c 2007-05-30 16:16:58.000000000 +0400
+++ linux-2.6.22-rc2-mm1-0/kernel/res_counter.c 2007-05-30 16:13:09.000000000 +0400
@@ -0,0 +1,73 @@
+/*
+ * resource containers
+ *
+ * Copyright 2007 OpenVZ SWsoft Inc
+ *
+ * Author: Pavel Emelianov <xemul@openvz.org>
+ *
+ */
+
+
+#include <linux/types.h>
+#include <linux/parser.h>
+#include <linux/fs.h>
+#include <linux/res_counter.h>

```

```

+ #include <asm/uaccess.h>
+
+ static inline unsigned long *res_counter_member(struct res_counter *cnt, int member)
+ {
+     switch (member) {
+     case RES_USAGE:
+         return &cnt->usage;
+     case RES_LIMIT:
+         return &cnt->limit;
+     case RES_FAILCNT:
+         return &cnt->failcnt;
+     };
+
+     BUG();
+     return NULL;
+ }
+
+ ssize_t res_counter_read(struct res_counter *cnt, int member,
+     const char __user *userbuf, size_t nbytes, loff_t *pos)
+ {
+     unsigned long *val;
+     char buf[64], *s;
+
+     s = buf;
+     val = res_counter_member(cnt, member);
+     s += sprintf(s, "%lu\n", *val);
+     return simple_read_from_buffer((void __user *)userbuf, nbytes,
+         pos, buf, s - buf);
+ }
+
+ ssize_t res_counter_write(struct res_counter *cnt, int member,
+     const char __user *userbuf, size_t nbytes, loff_t *pos)
+ {
+     int ret;
+     char *buf, *end;
+     unsigned long tmp, *val;
+
+     buf = kmalloc(nbytes + 1, GFP_KERNEL);
+     ret = -ENOMEM;
+     if (buf == NULL)
+         goto out;
+
+     buf[nbytes] = 0;
+     ret = -EFAULT;
+     if (copy_from_user(buf, userbuf, nbytes))
+         goto out_free;
+
+     ret = -EINVAL;

```

```
+ tmp = simple_strtoul(buf, &end, 10);
+ if (*end != '\0')
+ goto out_free;
+
+ val = res_counter_member(cnt, member);
+ *val = tmp;
+ ret = nbytes;
+out_free:
+ kfree(buf);
+out:
+ return ret;
+}
```
