
Subject: Re: IPv6 again but this time with veth
Posted by [Jan Tomasek](#) on Fri, 29 Jun 2007 08:23:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

Oh. I got lost! Could I try to describe it again?

My HW node is staj-dev:

```
auto eth0
iface eth0 inet static
    address 195.113.233.4
    netmask 255.255.255.0
    network 195.113.233.0
    broadcast 195.113.233.255
    gateway 195.113.233.1
    dns-nameservers 195.113.144.233 195.113.144.194
    dns-search cesnet.cz

iface eth0 inet6 static
    post-up /sbin/sysctl -w "net.ipv6.conf.eth0.autoconf=0"
    address 2001:718:1:e::23:3004
    netmask 64
```

My VE node, has this config (ip6v2-test):

```
auto eth0
iface eth0 inet static
    address 195.113.233.12
    netmask 255.255.255.0
    network 195.113.233.0
    broadcast 195.113.233.255
    gateway 195.113.233.4
    dns-nameservers 195.113.144.233 195.113.144.194
    dns-search cesnet.cz
```

```
eth0 inet6 static
    iface eth0 inet6 static
    address 2001:718:1:e::23:3012
    netmask 64
```

After executing:

```
brctl addbr vzbr0
brctl addif vzbr0 veth012.0
ifconfig vzbr0 0
echo 1 > /proc/sys/net/ipv4/conf/vzbr0/forwarding
echo 1 > /proc/sys/net/ipv4/conf/vzbr0/proxy_arp
```

```

echo 1 > /proc/sys/net/ipv4/conf/eth0/forwarding
echo 1 > /proc/sys/net/ipv4/conf/eth0/proxy_arp
ip route add 195.113.233.12 dev vzbr0
ip route add 2001:718:1:e::23:3012 dev vzbr0

```

****MARK****

VE starts to be reachable from Internet on IPv4. What should I do next?

```

echo 1 > /proc/sys/net/ipv6/conf/eth0/forwarding

```

somehow broke IPv6 for HW node.

```

echo 1 > /proc/sys/net/ipv6/conf/vzbr0/forwarding

```

cause no problem.

Well - returning to point marked as ****MARK****.

Route table on HW node:

```

> staj-dev:~# route -6
> Kernel IPv6 routing table
> Destination                Next Hop
> ::1/128                    ::
> 2001:718:1:e::23:3004/128  ::
> 2001:718:1:e::23:3012/128  ::
> 2001:718:1:e::/64          ::
> fe80::/128                 ::
> fe80::1/128                ::
> fe80::20c:29ff:fe63:a674/128 ::
> fe80::20c:29ff:fe63:a674/128 ::
> fe80::213:72ff:fe1b:b97/128 ::
> fe80::/64                  ::
> fe80::/64                  ::
> fe80::/64                  ::
> fe80::/64                  ::
> f020::1/128                ff02::1
> ff00::/8                   ::
> ff00::/8                   ::
> ff00::/8                   ::
> ff00::/8                   ::
> ::/0                       fe80::215:faff:fe87:3100

```

Flags	Metric	Ref	Use	Iface
U	0	6	1	lo
U	0	788	1	lo
U	1024	0	0	vzbr0
U	256	169	0	eth0
U	0	0	2	lo
U	0	0	1	lo
U	0	0	1	lo
U	0	0	1	lo
U	0	32	1	lo
U	256	0	0	eth0
U	256	0	0	venet0
U	256	0	0	veth012.0
U	256	0	0	vzbr0
UC	0	165	0	eth0
U	256	0	0	eth0
U	256	0	0	venet0
U	256	0	0	veth012.0
U	256	0	0	vzbr0
UGDA	1024	167	0	eth0

Route table on VE node:

```

> root@ip6v2-test:/# route -6
> Kernel IPv6 routing table

```

> Destination	Next Hop	Flags	Metric	Ref	Use	Iface
> ::1/128	::	U	0	1	1	lo
> 2001:718:1:e::23:3012/128	::	U	0	53	1	lo
> 2001:718:1:e::/64	::	U	256	0	0	eth0
> fe80::20c:29ff:fe63:a673/128	::	U	0	0	1	lo
> fe80::/64	::	U	256	0	0	eth0
> ff00::/8	::	U	256	0	0	eth0

VE is missing default GW, I expect it to show there somehow automatically like in HW node... maybe this is one of my bugs.

When I try to ping my HW node, for that I've routes there I get:

```
> root@ip6v2-test:/# ping6 2001:718:1:e::23:3004
> PING 2001:718:1:e::23:3004(2001:718:1:e::23:3004) 56 data bytes
> From 2001:718:1:e::23:3012 icmp_seq=1 Destination unreachable: Address unreachable
> From 2001:718:1:e::23:3012 icmp_seq=2 Destination unreachable: Address unreachable
```

and on HW node:

```
> stj-dev:~# tcpdump -i vzbr0
> tcpdump: WARNING: vzbr0: no IPv4 address assigned
> tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
> listening on vzbr0, link-type EN10MB (Ethernet), capture size 96 bytes
> 11:23:40.306129 IP6 2001:718:1:e::23:3012 > ff02::1:ff23:3004: ICMP6, neighbor solicitation,
who has stj-dev6.cesnet.cz, length 32
> 11:23:41.305975 IP6 2001:718:1:e::23:3012 > ff02::1:ff23:3004: ICMP6, neighbor solicitation,
who has stj-dev6.cesnet.cz, length 32
```

When I try opposite direction:

```
> stj-dev:~# ping6 2001:718:1:e::23:3012
> PING 2001:718:1:e::23:3012(2001:718:1:e::23:3012) 56 data bytes
> [... no output at all ...]

> root@ip6v2-test:/# tcpdump -n -i eth0
> tcpdump: verbose output suppressed, use -v or -vv for full protocol decode
> listening on eth0, link-type EN10MB (Ethernet), capture size 96 bytes
> 09:32:01.755512 IP6 2001:718:1:e::23:3012 > ff02::1:ff23:3004: ICMP6, neighbor solicitation,
who has 2001:718:1:e::23:3004, length 32
> 09:32:01.755721 IP6 2001:718:1:e::23:3004 > 2001:718:1:e::23:3012: ICMP6, echo request,
seq 27, length 64
> 09:32:02.756372 IP6 2001:718:1:e::23:3004 > 2001:718:1:e::23:3012: ICMP6, echo request,
seq 28, length 64
> 09:32:02.757356 IP6 2001:718:1:e::23:3012 > ff02::1:ff23:3004: ICMP6, neighbor solicitation,
who has 2001:718:1:e::23:3004, length 32
> 09:32:03.756222 IP6 2001:718:1:e::23:3004 > 2001:718:1:e::23:3012: ICMP6, echo request,
seq 29, length 64
```

> 09:32:03.757208 IP6 2001:718:1:e::23:3012 > ff02::1:ff23:3004: ICMP6, neighbor solicitation, who has 2001:718:1:e::23:3004, length 32
> 09:32:04.756070 IP6 2001:718:1:e::23:3004 > 2001:718:1:e::23:3012: ICMP6, echo request, seq 30, length 64
> 09:32:04.757057 IP6 2001:718:1:e::23:3012 > ff02::1:ff23:3004: ICMP6, neighbor solicitation, who has 2001:718:1:e::23:3004, length 32
> 09:32:05.755924 IP6 2001:718:1:e::23:3004 > 2001:718:1:e::23:3012: ICMP6, echo request, seq 31, length 64
> 09:32:06.755787 IP6 2001:718:1:e::23:3004 > 2001:718:1:e::23:3012: ICMP6, echo request, seq 32, length 64
> 09:32:06.756762 IP6 2001:718:1:e::23:3012 > ff02::1:ff23:3004: ICMP6, neighbor solicitation, who has 2001:718:1:e::23:3004, length 32

Any thoughts, please?

--

Jan Tomasek aka Semik
<http://www.tomasek.cz/>
