
Subject: Debian etch 2.6.18-028stab021 + dovecot
Posted by [weldpua2008](#) on Mon, 02 Jul 2007 22:11:39 GMT
[View Forum Message](#) <> [Reply to Message](#)

Debian etch 2.6.18-028stab021

```
#dovecot --version  
1.0.rc15
```

```
dovecot: 2007-06-23 17:53:51 Error: auth(default):  
net_connect_unix(/var/run/dovecot/auth-worker.11920) failed:Cannot allocate memory  
dovecot: 2007-06-23 17:54:19 Error: pop3-login: Can't connect to auth server at default: Cannot  
allocate memory
```

Quote:the only plausible reason for "Cannot allocate memory" is that the kernel is really running out of memory and for this reason, I'm closing the bug report.

```
-----  
# cat dovecot.conf |grep -v '#'  
base_dir = /var/run/dovecot/  
protocols = imap imaps pop3 pop3s  
listen = *  
disable_plaintext_auth = no  
shutdown_clients = yes  
log_path = /var/log/exim4/dovecot.log  
log_timestamp = "%Y-%m-%d %H:%M:%S "  
ssl_disable = yes  
login_dir = /var/run/dovecot/login  
login_chroot = yes  
login_user = dovecot  
login_process_per_connection = yes  
login_processes_count = 3  
login_max_processes_count = 512  
login_max_connections = 256
```

```
login_greeting = Dovecot ready.
mail_location = maildir:/var/mail/%d/%n/Maildir
mail_extra_groups = mail
first_valid_uid = 1
last_valid_uid = 0
first_valid_gid = 1
last_valid_gid = 0
max_mail_processes = 1024
mbox_lock_timeout = 300
protocol imap {
}
protocol pop3 {
  pop3_uidl_format = %08Xu%08Xv
}
auth default {
  passdb pam {
  }
  passdb sql {
    args = /etc/dovecot/dovecot-sql.conf
  }
  userdb sql {
    args = /etc/dovecot/dovecot-sql.conf
  }
  user = root
  ssl_require_client_cert = no
  ssl_username_from_cert = no
}
dict {
}
plugin {
}
```

```
# cat dovecot-sql.conf |grep -v '#'
```

```
driver = mysql
connect = host=127.0.0.1 dbname=somedb user=dovecot password=password
```

```
default_pass_scheme = CRYPT
password_query = SELECT crypt as password FROM users,domains WHERE users.localpart =
'%n' AND users.domain_id =
domains.domain_id AND domains.domain='%d' AND users.enabled = '1'
user_query = SELECT users.uid as uid, users.gid as gid FROM users,domains WHERE
users.localpart = '%n' AND users.domain_id
= domains.domain_id AND domains.domain='%d'
```

```
#cat dovecot-mysql.conf |grep -v '#'
```

```
db_host = localhost
db_port = 3306
db = somedb
db_user = dovecot
db_passwd password
db_client_flags = 0
password_query = SELECT crypt FROM users,domains WHERE users.localpart = '%n' AND
users.domain_id = domains.domain_id AND
domains.domain='%d' AND users.enabled = '1'
user_query = SELECT users.uid, users.gid FROM users,domains WHERE users.localpart = '%n'
AND users.domain_id =
domains.domain_id AND domains.domain='%d'
```
