Subject: Re: VEs with different subnets
Posted by ugo123 on Tue, 03 Jul 2007 09:26:36 GMT
View Forum Message <> Reply to Message

```
mercury:~# ip r l
87.98.196.137 dev venet0  scope link  src 10.1.1.14
87.98.196.128/26 dev eth0  scope link
10.1.0.0/16 dev eth0  proto kernel  scope link  src 10.1.1.14
default via 10.1.1.1 dev eth0
mercury:~# ip a l
2: bond0: <BROADCAST,MULTICAST,MASTER> mtu 1500 qdisc noop
    link/ether 00:00:00:00:00:00 brd ff:ff:ff:ff:ff:ff
4: lo: <LOOPBACK,UP,10000> mtu 16436 qdisc noqueue
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
    inet6 ::1/128 scope host
      valid_lft forever preferred_lft forever
6: eth0: <BROADCAST,MULTICAST,UP,10000> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 00:50:70:26:57:37 brd ff:ff:ff:ff:ff:ff
    inet 10.1.1.14/16 brd 10.1.255.255 scope global eth0
    inet6 fe80::250:70ff:fe26:5737/64 scope link
      valid_lft forever preferred_lft forever
8: dummy0: <BROADCAST,NOARP> mtu 1500 qdisc noop
    link/ether e6:1f:aa:72:10:de brd ff:ff:ff:ff:ff:ff
10: teql0: <NOARP> mtu 1500 qdisc noop qlen 100
    link/void
12: tunl0: <NOARP> mtu 1480 qdisc noop
    link/ipip 0.0.0.0 brd 0.0.0.0
14: gre0: <NOARP> mtu 1476 qdisc noop
    link/gre 0.0.0.0 brd 0.0.0.0
16: sit0: <NOARP> mtu 1480 qdisc noop
    link/sit 0.0.0.0 brd 0.0.0.0
18: ip6tnl0: <NOARP> mtu 1460 qdisc noop
    link/tunnel6 00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00 brd
00:00:00:00:00:00:00:00:00:00:00:00:00:00:00:00
1: venet0: <BROADCAST,POINTOPOINT,NOARP,UP,10000> mtu 1500 qdisc noqueue
    link/void
mercury:~#
```