

---

Subject: [PATCH] single\_open/seq\_release leak diagnostics  
Posted by [Alexey Dobriyan](#) on Tue, 31 Jul 2007 12:05:26 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

"[PATCH] Fix leaks on /proc/{\*/sched,sched\_debug,timer\_list,timer\_stats}" and  
"[PATCH] Fix leak on /proc/lockdep\_stats" fixed 5 leaks which happen if one  
uses single\_open() as .open function and seq\_release() as .release function.

Let's add small amount of runtime checking.

Sample output is:

```
memory leak: 'timer_list'  
WARNING: at fs/seq_file.c:289 seq_release()  
[<c015e311>] seq_release+0x53/0x68  
[<c0171bd8>] proc_reg_release+0x63/0x74  
[<c0149877>] __fput+0x28/0xd3  
[<c0147681>] filp_close+0x48/0x4f  
[<c014876a>] sys_close+0x74/0xbe  
[<c010248e>] sysenter_past_esp+0x5f/0x85  
=====
```

Signed-off-by: Alexey Dobriyan <[adobriyan@sw.ru](mailto:adobriyan@sw.ru)>

---

```
fs/seq_file.c      | 25 ++++++-----  
include/linux/seq_file.h |  1 +  
2 files changed, 21 insertions(+), 5 deletions(-)
```

```
--- a/fs/seq_file.c  
+++ b/fs/seq_file.c  
@@ -281,6 +281,13 @@ EXPORT_SYMBOL(seq_lseek);  
int seq_release(struct inode *inode, struct file *file)  
{  
    struct seq_file *m = (struct seq_file *)file->private_data;  
+  
+    if (m->seq_ops_allocated) {  
+        struct dentry *dentry = file->f_dentry;  
+        printk("memory leak: '%.*s'\n",  
+              dentry->d_name.len, dentry->d_name.name);  
+        WARN_ON(1);  
+    }  
    kfree(m->buf);  
    kfree(m);  
    return 0;  
@@ -401,9 +408,12 @@ int single_open(struct file *file, int (*show)(struct seq_file *, void *),  
    op->stop = single_stop;  
    op->show = show;
```

```

res = seq_open(file, op);
- if (!res)
-   ((struct seq_file *)file->private_data)->private = data;
- else
+ if (!res) {
+   struct seq_file *seq = file->private_data;
+
+   seq->private = data;
+   seq->seq_ops_allocated = 1;
+ } else
  kfree(op);
}
return res;
@@ -412,8 +422,13 @@ EXPORT_SYMBOL(single_open);

```

```

int single_release(struct inode *inode, struct file *file)
{
- const struct seq_operations *op = ((struct seq_file *)file->private_data)->op;
- int res = seq_release(inode, file);
+ struct seq_file *seq = file->private_data;
+ const struct seq_operations *op = seq->op;
+ int res;
+
+ /* All roads lead to seq_release(), so... */
+ seq->seq_ops_allocated = 0;
+ res = seq_release(inode, file);
  kfree(op);
  return res;
}
--- a/include/linux/seq_file.h
+++ b/include/linux/seq_file.h
@@ -22,6 +22,7 @@ struct seq_file {
  struct mutex lock;
  const struct seq_operations *op;
  void *private;
+ unsigned int seq_ops_allocated:1;
};

struct seq_operations {

```

---