

---

Subject: Tweak /proc/ipmi removal  
Posted by [Alexey Dobriyan](#) on Fri, 03 Aug 2007 13:30:18 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Driver does

```
proc_mkdir("ipmi", NULL);  
but  
remove_proc_entry(proc_ipmi_root->name, &proc_root);
```

This is OK and working if only slightly inconsistent.

Also changing proc\_root to NULL will help OpenVZ which has multiple proc roots and, as we now know, requires matching parents in such cases.

Please, apply.

Signed-off-by: Alexey Dobriyan <[adobriyan@sw.ru](mailto:adobriyan@sw.ru)>

---

```
drivers/char/ipmi/ipmi_msghandler.c |  2 +-  
1 file changed, 1 insertion(+), 1 deletion(-)  
  
--- a/drivers/char/ipmi/ipmi_msghandler.c  
+++ b/drivers/char/ipmi/ipmi_msghandler.c  
@@ -4136,7 +4136,7 @@ static __exit void cleanup_ipmi(void)  
    del_timer_sync(&ipmi_timer);  
  
#ifdef CONFIG_PROC_FS  
- remove_proc_entry(proc_ipmi_root->name, &proc_root);  
+ remove_proc_entry(proc_ipmi_root->name, NULL);  
#endif /* CONFIG_PROC_FS */  
  
driver_unregister(&ipmidriver);
```

---