## Subject: Re: [PATCH/RFC] kthread API conversion for dvb\_frontend and av7110 Posted by Herbert Poetzl on Thu, 14 Sep 2006 22:10:24 GMT

View Forum Message <> Reply to Message

```
On Thu, Sep 14, 2006 at 11:07:49PM +0200, Cedric Le Goater wrote:
> Herbert Poetzl wrote:
> > Okay, as I promised, I had a first shot at the
> > dvb kernel_thread to kthread API port, and here
> > is the result, which is running fine here since
> > yesterday, including module load/unload and
> > software suspend (which doesn't work as expected
> > with or without this patch :),
>
> So you have such an hardware?
yes, I do .. that's how I tested it :)
>[...]
>> @ @ -600,7 +595,6 @ @ static int dvb_frontend_thread(void *dat
>> static void dvb frontend stop(struct dvb frontend *fe)
>> {
>> - unsigned long ret:
>> struct dvb_frontend_private *fepriv = fe->frontend_priv;
> >
>> dprintk ("%s\n", __FUNCTION__);
>> @ @ -608,33 +602,17 @ @ static void dvb frontend stop(struct dvb
>> fepriv->exit = 1;
> do we still need the ->exit flag now that we are using kthread stop()?
> same question for ->wakeup?
probably not, but I didn't want to change too
much on the first try, especially I'd appreciate
some feedback to this from the maintainer(s)
> > mb();
>> - if (!fepriv->thread_pid)
> > - return;
>> - /* check if the thread is really alive */
>> - if (kill_proc(fepriv->thread_pid, 0, 1) == -ESRCH) {
>> - printk("dvb_frontend_stop: thread PID %d already died\n",
> > - fepriv->thread_pid);
>> - /* make sure the mutex was not held by the thread */
>> - init MUTEX (&fepriv->sem);
```

```
> > + if (!fepriv->thread)
>> return;
>>-}
>>-
>> - /* wake up the frontend thread, so it notices that fe->exit == 1 */
> > - dvb_frontend_wakeup(fe);
> >
>> - /* wait until the frontend thread has exited */
>> - ret = wait event interruptible(fepriv->wait queue,0 == fepriv->thread pid);
> > - if (-ERESTARTSYS != ret) {
>> - fepriv->state = FESTATE IDLE;
>> - return:
>> - }
> > + kthread_stop(fepriv->thread);
> > + init_MUTEX (&fepriv->sem);
>
> the use of the semaphore to synchronise the thread is complex. It will
> require extra care to avoid deadlocks.
well, it 'works' quite fine for now, but yeah, I
thought about completely removing the additional
synchronization and 'jsut' go with the kthread
one, if that is sufficient ...
>> fepriv->state = FESTATE_IDLE;
> >
>> /* paranoia check in case a signal arrived */
>> - if (fepriv->thread pid)
>> - printk("dvb frontend stop: warning: thread PID %d won't exit\n",
>> - fepriv->thread pid);
> > + if (fepriv->thread)
>> + printk("dvb frontend stop: warning: thread %p won't exit\n",
>> + fepriv->thread);
> kthread_stop uses a completion already, so the above is real paranoia:)
again, I think this will go away soon:)
>> }
> >
>> s32 timeval usec diff(struct timeval lasttime, struct timeval curtime)
>> @ @ -684,10 +662,11 @ @ static int dvb_frontend_start(struct dvb
>> {
>> int ret;
>> struct dvb_frontend_private *fepriv = fe->frontend_priv;
> > + struct task_struct *fe_thread;
> >
>> dprintk ("%s\n", __FUNCTION__);
```

```
> >
> > - if (fepriv->thread_pid) {
> > + if (fepriv->thread) {
    if (!fepriv->exit)
      return 0;
> >
     else
>>
>> @ @ -701,18 +680,18 @ @ static int dvb_frontend_start(struct dvb
>> fepriv->state = FESTATE_IDLE;
>> fepriv->exit = 0;
>> - fepriv->thread_pid = 0;
> > + fepriv->thread = NULL;
>> mb();
> > - ret = kernel_thread (dvb_frontend_thread, fe, 0);
>> - if (ret < 0) {
>> - printk("dvb_frontend_start: failed to start kernel_thread (%d)\n", ret);
> > + fe_thread = kthread_run(dvb_frontend_thread, fe,
> > + "kdvb-fe-%i", fe->dvb->num);
> > + if (IS_ERR(fe_thread)) {
>> + ret = PTR ERR(fe thread);
> ret could be local.
correct, will fix that up in the next round
thanks for the feedback,
Herbert
>[...]
>
> Containers mailing list
> Containers@lists.osdl.org
> https://lists.osdl.org/mailman/listinfo/containers
Containers mailing list
Containers@lists.osdl.org
https://lists.osdl.org/mailman/listinfo/containers
```