
Subject: [PATCH] Use kill_cad_pid() in ip22-reset.c
Posted by [Sukadev Bhattiprolu](#) on Tue, 19 Sep 2006 22:49:51 GMT
[View Forum Message](#) <> [Reply to Message](#)

This is very similar to Cedric's change to ip32-reset.c in the cad_pid patch.

Suka

Use kill_cad_pid() to signal the init process instead of the hard coded pid 1.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: containers@lists.osdl.org

arch/mips/sgi-ip22/ip22-reset.c | 2 +-
1 file changed, 1 insertion(+), 1 deletion(-)

Index: lx26-18-rc6-mm2/arch/mips/sgi-ip22/ip22-reset.c

```
=====
--- lx26-18-rc6-mm2.orig/arch/mips/sgi-ip22/ip22-reset.c 2006-09-19 15:37:58.000000000 -0700
+++ lx26-18-rc6-mm2/arch/mips/sgi-ip22/ip22-reset.c 2006-09-19 15:38:20.000000000 -0700
@@ -123,7 +123,7 @@ static inline void power_button(void)
     if (machine_state & MACHINE_PANICED)
         return;

- if ((machine_state & MACHINE_SHUTTING_DOWN) || kill_proc(1, SIGINT, 1)) {
+ if ((machine_state & MACHINE_SHUTTING_DOWN) || kill_cad_pid(SIGINT, 1)) {
     /* No init process or button pressed twice. */
     sgi_machine_power_off();
 }
```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
