
Subject: Re: namespace and nsproxy syscalls
Posted by [serue](#) on Tue, 26 Sep 2006 12:56:49 GMT
[View Forum Message](#) <> [Reply to Message](#)

Quoting Cedric Le Goater (clg@fr.ibm.com):

> Hello all,
>
> A while ago, we expressed the need to have a new syscall specific to
> namespaces. the clone and unshare are good candidates but we are reaching
> the limit of the clone flags and clone has been hijacked enough.
>
> So, I came up with unshare_ns. the patch for the core feature follows
> the email. Not much difference with unshare() for the moment but it gives
> us the freedom to diverge when new namespaces come in. I have faith also !
> If you feel it's useful, i'll send the full patchset for review on the list.
>
> I'd like to discuss of another syscall which would allow a process to
> bind to a set of namespaces (== nsproxy == container) :
>
> bind_ns(ns_id_t id, int flags)

What about just using a pid instead of introducing some ns_id_t? I'm guessing that any time you want to bind to some other nsproxy, it will be the nsproxy of a decendent nsproxy, so even if it is in a new pidspace, you will have a pid in your pidspace to reference it.

-serge

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
