
Subject: [Lxc-devel] - pidspac-is_init.patch removed from -mm tree

Posted by [Andrew Morton](#) on Fri, 29 Sep 2006 19:58:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

The patch titled

pidspac: is_init()

has been removed from the -mm tree. Its filename is

pidspac-is_init.patch

This patch was dropped because it was merged into mainline or a subsystem tree

Subject: pidspac: is_init()
From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

This is an updated version of Eric Biederman's is_init() patch.
(<http://lkml.org/lkml/2006/2/6/280>). It applies cleanly to 2.6.18-rc3 and
replaces a few more instances of ->pid == 1 with is_init().

Further, is_init() checks pid and thus removes dependency on Eric's other
patches for now.

Eric's original description:

There are a lot of places in the kernel where we test for init
because we give it special properties. Most significantly init
must not die. This results in code all over the kernel test
->pid == 1.

Introduce is_init to capture this case.

With multiple pid spaces for all of the cases affected we are
looking for only the first process on the system, not some other
process that has pid == 1.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Cc: Dave Hansen <haveblue@us.ibm.com>

Cc: Serge Hallyn <serue@us.ibm.com>

Cc: Cedric Le Goater <cclg@fr.ibm.com>

Cc: <lxc-devel@lists.sourceforge.net>

Acked-by: Paul Mackerras <paulus@samba.org>

Signed-off-by: Andrew Morton <akpm@osdl.org>

```

arch/alpha/mm/fault.c      | 2 ++
arch/arm/mm/fault.c       | 2 ++
arch/arm26/mm/fault.c     | 2 ++
arch/i386/lib/usercopy.c   | 2 ++
arch/i386/mm/fault.c      | 2 ++
arch/ia64/mm/fault.c      | 2 ++
arch/m32r/mm/fault.c      | 2 ++
arch/m68k/mm/fault.c      | 2 ++
arch/mips/mm/fault.c      | 2 ++
arch/powerpc/mm/fault.c   | 2 ++
arch/powerpc/platforms/pseries/ras.c | 2 ++
arch/ppc/kernel/traps.c    | 2 ++
arch/ppc/mm/fault.c       | 2 ++
arch/s390/mm/fault.c      | 2 ++
arch/sh/mm/fault.c        | 2 ++
arch/sh64/mm/fault.c      | 6 +++++-
arch/um/kernel/trap.c      | 2 ++
arch/x86_64/mm/fault.c    | 4 +---
arch/xtensa/mm/fault.c    | 2 ++
drivers/char/sysrq.c      | 2 ++
include/linux/sched.h      | 10 ++++++++
kernel/capability.c       | 2 ++
kernel/cpuset.c           | 2 ++
kernel/exit.c              | 2 ++
kernel/kexec.c             | 2 ++
kernel/ptrace.c            | 1 +
kernel/sysctl.c            | 2 ++
mm/oom_kill.c              | 2 ++
security/commoncap.c       | 2 ++
29 files changed, 41 insertions(+), 30 deletions(-)

```

```

diff -puN arch/alpha/mm/fault.c~pidspace-is_init arch/alpha/mm/fault.c
--- a/arch/alpha/mm/fault.c~pidspace-is_init
+++ a/arch/alpha/mm/fault.c
@@ -193,7 +193,7 @@ do_page_fault(unsigned long address, uns
 /* We ran out of memory, or some other thing happened to us that
 made us unable to handle the page fault gracefully. */
out_of_memory:
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/arm/mm/fault.c~pidspace-is_init arch/arm/mm/fault.c
--- a/arch/arm/mm/fault.c~pidspace-is_init
+++ a/arch/arm/mm/fault.c
@@ -198,7 +198,7 @@ survive:
    return fault;

```

```

}

- if (tsk->pid != 1)
+ if (!is_init(tsk))
    goto out;

/*
diff -puN arch/arm26/mm/fault.c~pidspace-is_init arch/arm26/mm/fault.c
--- a/arch/arm26/mm/fault.c~pidspace-is_init
+++ a/arch/arm26/mm/fault.c
@@ -185,7 +185,7 @@ survive:
}

fault = -3; /* out of memory */
- if (tsk->pid != 1)
+ if (!is_init(tsk))
    goto out;

/*
diff -puN arch/i386/lib/usercopy.c~pidspace-is_init arch/i386/lib/usercopy.c
--- a/arch/i386/lib/usercopy.c~pidspace-is_init
+++ a/arch/i386/lib/usercopy.c
@@ -739,7 +739,7 @@ survive:
    retval = get_user_pages(current, current->mm,
        (unsigned long )to, 1, 1, 0, &pg, NULL);

- if (retval == -ENOMEM && current->pid == 1) {
+ if (retval == -ENOMEM && is_init(current)) {
    up_read(&current->mm->mmap_sem);
    blk_congestion_wait(WRITE, HZ/50);
    goto survive;
diff -puN arch/i386/mm/fault.c~pidspace-is_init arch/i386/mm/fault.c
--- a/arch/i386/mm/fault.c~pidspace-is_init
+++ a/arch/i386/mm/fault.c
@@ -589,7 +589,7 @@ no_context:
*/
out_of_memory:
    up_read(&mm->mmap_sem);
- if (tsk->pid == 1) {
+ if (is_init(tsk)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/ia64/mm/fault.c~pidspace-is_init arch/ia64/mm/fault.c
--- a/arch/ia64/mm/fault.c~pidspace-is_init
+++ a/arch/ia64/mm/fault.c
@@ -280,7 +280,7 @@ ia64_do_page_fault (unsigned long address

```

```

out_of_memory:
up_read(&mm->mmap_sem);
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/m32r/mm/fault.c~pidspace-is_init arch/m32r/mm/fault.c
--- a/arch/m32r/mm/fault.c~pidspace-is_init
+++ a/arch/m32r/mm/fault.c
@@ -299,7 +299,7 @@ no_context:
 */
out_of_memory:
up_read(&mm->mmap_sem);
- if (tsk->pid == 1) {
+ if (is_init(tsk)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/m68k/mm/fault.c~pidspace-is_init arch/m68k/mm/fault.c
--- a/arch/m68k/mm/fault.c~pidspace-is_init
+++ a/arch/m68k/mm/fault.c
@@ -181,7 +181,7 @@ good_area:
 */
out_of_memory:
up_read(&mm->mmap_sem);
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/mips/mm/fault.c~pidspace-is_init arch/mips/mm/fault.c
--- a/arch/mips/mm/fault.c~pidspace-is_init
+++ a/arch/mips/mm/fault.c
@@ -171,7 +171,7 @@ no_context:
 */
out_of_memory:
up_read(&mm->mmap_sem);
- if (tsk->pid == 1) {
+ if (is_init(tsk)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/powerpc/mm/fault.c~pidspace-is_init arch/powerpc/mm/fault.c
--- a/arch/powerpc/mm/fault.c~pidspace-is_init
+++ a/arch/powerpc/mm/fault.c
@@ -386,7 +386,7 @@ bad_area_nosemaphore:
 */

```

```

out_of_memory:
    up_read(&mm->mmap_sem);
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/powerpc/platforms/pseries/ras.c~pidspace-is_init
arch/powerpc/platforms/pseries/ras.c
--- a/arch/powerpc/platforms/pseries/ras.c~pidspace-is_init
+++ a/arch/powerpc/platforms/pseries/ras.c
@@ @ -337,7 +337,7 @@ static int recover_mce(struct pt_regs *r
    err->disposition == RTAS_DISP_NOT_RECOVERED &&
    err->target == RTAS_TARGET_MEMORY &&
    err->type == RTAS_TYPE_ECC_UNCORR &&
-   !(current->pid == 0 || current->pid == 1)) {
+   !(current->pid == 0 || is_init(current))) {
    /* Kill off a user process with an ECC error */
    printk(KERN_ERR "MCE: uncorrectable ecc error for pid %d\n",
           current->pid);
diff -puN arch/ppc/kernel/traps.c~pidspace-is_init arch/ppc/kernel/traps.c
--- a/arch/ppc/kernel/traps.c~pidspace-is_init
+++ a/arch/ppc/kernel/traps.c
@@ @ -119,7 +119,7 @@ void _exception(int signr, struct pt_reg
    * generate the same exception over and over again and we get
    * nowhere. Better to kill it and let the kernel panic.
    */
- if (current->pid == 1) {
+ if (is_init(current)) {
    __sighandler_t handler;

    spin_lock_irq(&current->sighand->siglock);
diff -puN arch/ppc/mm/fault.c~pidspace-is_init arch/ppc/mm/fault.c
--- a/arch/ppc/mm/fault.c~pidspace-is_init
+++ a/arch/ppc/mm/fault.c
@@ @ -291,7 +291,7 @@ bad_area:
    */
out_of_memory:
    up_read(&mm->mmap_sem);
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/s390/mm/fault.c~pidspace-is_init arch/s390/mm/fault.c
--- a/arch/s390/mm/fault.c~pidspace-is_init
+++ a/arch/s390/mm/fault.c
@@ @ -353,7 +353,7 @@ no_context:

```

```

*/
out_of_memory:
    up_read(&mm->mmap_sem);
- if (tsk->pid == 1) {
+ if (is_init(tsk)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/sh/mm/fault.c~pidspace-is_init arch/sh/mm/fault.c
--- a/arch/sh/mm/fault.c~pidspace-is_init
+++ a/arch/sh/mm/fault.c
@@@ -149,7 +149,7 @@@ no_context:
 */
out_of_memory:
    up_read(&mm->mmap_sem);
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN arch/sh64/mm/fault.c~pidspace-is_init arch/sh64/mm/fault.c
--- a/arch/sh64/mm/fault.c~pidspace-is_init
+++ a/arch/sh64/mm/fault.c
@@@ -277,7 +277,7 @@@ bad_area:
    show_regs(regs);
#endif
}
- if (tsk->pid == 1) {
+ if (is_init(tsk)) {
    panic("INIT had user mode bad_area\n");
}
    tsk->thread.address = address;
@@@ -319,14 +319,14 @@@ no_context:
    * us unable to handle the page fault gracefully.
 */
out_of_memory:
- if (current->pid == 1) {
+ if (is_init(current)) {
    panic("INIT out of memory\n");
    yield();
    goto survive;
}
    printk("fault:Out of memory\n");
    up_read(&mm->mmap_sem);
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);

```

```

goto survive;
diff -puN arch/um/kernel/trap.c~pidspace-is_init arch/um/kernel/trap.c
--- a/arch/um/kernel/trap.c~pidspace-is_init
+++ a/arch/um/kernel/trap.c
@@ -120,7 +120,7 @@ out_nosemaphore:
 * us unable to handle the page fault gracefully.
 */
out_of_memory:
- if (current->pid == 1) {
+ if (is_init(current)) {
    up_read(&mm->mmap_sem);
    yield();
    down_read(&mm->mmap_sem);
diff -puN arch/x86_64/mm/fault.c~pidspace-is_init arch/x86_64/mm/fault.c
--- a/arch/x86_64/mm/fault.c~pidspace-is_init
+++ a/arch/x86_64/mm/fault.c
@@ -244,7 +244,7 @@ static int is_errata93(struct pt_regs *r

int unhandled_signal(struct task_struct *tsk, int sig)
{
- if (tsk->pid == 1)
+ if (is_init(tsk))
    return 1;
  if (tsk->ptrace & PT_PTRACED)
    return 0;
@@ -580,7 +580,7 @@ no_context:
*/
out_of_memory:
  up_read(&mm->mmap_sem);
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    goto again;
}
diff -puN arch/xtensa/mm/fault.c~pidspace-is_init arch/xtensa/mm/fault.c
--- a/arch/xtensa/mm/fault.c~pidspace-is_init
+++ a/arch/xtensa/mm/fault.c
@@ -144,7 +144,7 @@ bad_area:
*/
out_of_memory:
  up_read(&mm->mmap_sem);
- if (current->pid == 1) {
+ if (is_init(current)) {
    yield();
    down_read(&mm->mmap_sem);
    goto survive;
diff -puN drivers/char/sysrq.c~pidspace-is_init drivers/char/sysrq.c
--- a/drivers/char/sysrq.c~pidspace-is_init

```

```

+++ a/drivers/char/sysrq.c
@@ -208,7 +208,7 @@ static void send_sig_all(int sig)
    struct task_struct *p;

    for_each_process(p) {
-     if (p->mm && p->pid != 1)
+     if (p->mm && !is_init(p))
        /* Not swapper, init nor kernel thread */
        force_sig(sig, p);
    }
diff -puN include/linux/sched.h~pidspace-is_init include/linux/sched.h
--- a/include/linux/sched.h~pidspace-is_init
+++ a/include/linux/sched.h
@@ -1033,6 +1033,16 @@ static inline int pid_alive(struct task_
    return p->pids[PIDTYPE_PID].pid != NULL;
}

+/**
+ * is_init - check if a task structure is the first user space
+ *          task the kernel created.
+ * @p: Task structure to be checked.
+ */
+static inline int is_init(struct task_struct *tsk)
+{
+    return tsk->pid == 1;
+}
+
extern void free_task(struct task_struct *tsk);
#define get_task_struct(tsk) do { atomic_inc(&(tsk)->usage); } while(0)

diff -puN kernel/capability.c~pidspace-is_init kernel/capability.c
--- a/kernel/capability.c~pidspace-is_init
+++ a/kernel/capability.c
@@ -133,7 +133,7 @@ static inline int cap_set_all(kernel_cap
    int found = 0;

    do_each_thread(g, target) {
-     if (target == current || target->pid == 1)
+     if (target == current || is_init(target))
        continue;
    found = 1;
    if (security_capset_check(target, effective, inheritable,
diff -puN kernel/cpuset.c~pidspace-is_init kernel/cpuset.c
--- a/kernel/cpuset.c~pidspace-is_init
+++ a/kernel/cpuset.c
@@ -240,7 +240,7 @@ static struct super_block *cpuset_sb;
 * A cpuset can only be deleted if both its 'count' of using tasks
 * is zero, and its list of 'children' cpusets is empty. Since all

```

```

* tasks in the system use _some_ cpuset, and since there is always at
- * least one task in the system (init, pid == 1), therefore, top_cpuset
+ * least one task in the system (init), therefore, top_cpuset
* always has either children cpusets and/or using tasks. So we don't
* need a special hack to ensure that top_cpuset cannot be deleted.
*
diff -puN kernel/exit.c~pidspace-is_init kernel/exit.c
--- a/kernel/exit.c~pidspace-is_init
+++ a/kernel/exit.c
@@ -219,7 +219,7 @@ static int will_become_orphaned_pgrp(int
    do_each_task_pid(pgrp, PIDTYPE_PGID, p) {
        if (p == ignored_task
            || p->exit_state
-           || p->real_parent->pid == 1)
+           || is_init(p->real_parent))
            continue;
        if (process_group(p->real_parent) != pgrp
            && p->real_parent->signal->session == p->signal->session) {
diff -puN kernel/kexec.c~pidspace-is_init kernel/kexec.c
--- a/kernel/kexec.c~pidspace-is_init
+++ a/kernel/kexec.c
@@ -40,7 +40,7 @@ struct resource crashk_res = {

int kexec_should_crash(struct task_struct *p)
{
- if (in_interrupt() || !p->pid || p->pid == 1 || panic_on_oops)
+ if (in_interrupt() || !p->pid || is_init(p) || panic_on_oops)
    return 1;
    return 0;
}
diff -puN kernel/ptrace.c~pidspace-is_init kernel/ptrace.c
--- a/kernel/ptrace.c~pidspace-is_init
+++ a/kernel/ptrace.c
@@ -440,6 +440,7 @@ struct task_struct *ptrace_get_task_stru
    child = find_task_by_pid(pid);
    if (child)
        get_task_struct(child);
+
    read_unlock(&tasklist_lock);
    if (!child)
        return ERR_PTR(-ESRCH);
diff -puN kernel/sysctl.c~pidspace-is_init kernel/sysctl.c
--- a/kernel/sysctl.c~pidspace-is_init
+++ a/kernel/sysctl.c
@@ -1915,7 +1915,7 @@ int proc_dointvec_bset(ctl_table *table,
    return -EPERM;
}

```

```

- op = (current->pid == 1) ? OP_SET : OP_AND;
+ op = is_init(current) ? OP_SET : OP_AND;
    return do_proc_dointvec(table, write, filp, buffer, lenp, ppos,
        do_proc_dointvec_bset_conv, &op);
}
diff -puN mm/oom_kill.c~pidspace-is_init mm/oom_kill.c
--- a/mm/oom_kill.c~pidspace-is_init
+++ a/mm/oom_kill.c
@@@ -255,7 +255,7 @@ static struct task_struct *select_bad_pr
 */
static void __oom_kill_task(struct task_struct *p, const char *message)
{
- if (p->pid == 1) {
+ if (is_init(p)) {
    WARN_ON(1);
    printk(KERN_WARNING "tried to kill init!\n");
    return;
diff -puN security/commoncap.c~pidspace-is_init security/commoncap.c
--- a/security/commoncap.c~pidspace-is_init
+++ a/security/commoncap.c
@@@ -169,7 +169,7 @@ void cap_bprm_apply_creds (struct linux_
/* For init, we want to retain the capabilities set
 * in the init_task struct. Thus we skip the usual
 * capability rules */
- if (current->pid != 1) {
+ if (!is_init(current)) {
    current->cap_permitted = new_permitted;
    current->cap_effective =
        cap_intersect (new_permitted, bprm->cap_effective);

```

Patches currently in -mm which might be from sukadef@us.ibm.com are

origin.patch
 pids-coding-style-use-struct-pidmap.patch
 proc-readdir-race-fix-take-3-fix-1.patch
 move-pidmap-to-pspaceh.patch
 move-pidmap-to-pspaceh-fix.patch
 define-struct-pspace.patch
 proc-readdir-race-fix-take-3-fix-2.patch

Take Surveys. Earn Cash. Influence the Future of IT
 Join SourceForge.net's Techsay panel and you'll get the chance to share your
 opinions on IT & business topics through brief surveys -- and earn cash
<http://www.techsay.com/default.php?page=join.php&p=sourceforge&CID=DEVDEV>

Lxc-devel mailing list

Lxc-devel@lists.sourceforge.net

<https://lists.sourceforge.net/lists/listinfo/lxc-devel>
