
Subject: Processes with multiple pid_t values

Posted by [Sukadev Bhattiprolu](#) on Fri, 08 Dec 2006 21:23:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

A process that unshares its namespace gets a new pid_t in the child namespace. Similarly its process group and session leaders get new pid_ts in the child namespace right ?

i.e do the following pid_ts look reasonable when process 1234 unshares its pid namespace ?

PID PPID PGID SID

init pid ns 1234 1233 1230 1220

child pid ns 3 2 1 0

Assuming they are :-), we should expect find_pid() call with nr == 0, 1, or 2 in the child pid namespace to also work right ?

But processes 1220, 1230, 1233 are entered into the hash table based on their init pid ns values. And so the above find_pid() calls would not find the process we want.

i.e some processes have two pid_ts and we want to find them using either of the two values. The pid_hash table can obviously hash on one value.

We would need some serious changes to the pid_hash table to do this ???
(can we change the hash algorithm to generate a key based on all pid_ts a process has ????)

Or should we just keep track of these special processes (4 per namespace including the child reaper) in the namespace object - just like we treat the child_reaper special ?

Then find_pid() would have to check the namespace object in addition to hash table.

Appreciate any ideas/comments.

Suka

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
