

---

Subject: [patch 02/20] [Network namespace] Delete unused destroy variable

Posted by [Daniel Lezcano](#) on Sun, 10 Dec 2006 21:58:19 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

---

net/ipv4/fib\_hash.c | 7 +-----  
1 files changed, 1 insertion(+), 6 deletions(-)

Index: 2.6.19-rc6-mm2/net/ipv4/fib\_hash.c

```
=====
--- 2.6.19-rc6-mm2.orig/net/ipv4/fib_hash.c
+++ 2.6.19-rc6-mm2/net/ipv4/fib_hash.c
@@ -621,11 +621,6 @@ static int fn_flush_list(struct fn_zone
     struct hlist_node *node, *n;
     struct fib_node *f;
     int found = 0;
-#ifndef CONFIG_NET_NS
- const int destroy = 0;
-#else
- const int destroy = current_net_ns->destroying;
-#endif

     hlist_for_each_entry_safe(f, node, n, head, fn_hash) {
         struct fib_alias *fa, *fa_node;
@@ -637,7 +632,7 @@ static int fn_flush_list(struct fn_zone

         if (fi == NULL)
             continue;
- if (destroy || (fi->fib_flags&RTNH_F_DEAD)) {
+ if ((fi->fib_flags&RTNH_F_DEAD)) {
             write_lock_bh(&fib_hash_lock);
             list_del(&fa->fa_list);
             if (list_empty(&f->fn_alias)) {
```

--

---

Containers mailing list  
Containers@lists.osdl.org  
<https://lists.osdl.org/mailman/listinfo/containers>

---