
Subject: [PATCH 11/12] pid: Remove now unused do_each_task_pid and while_each_task_pid

Posted by [ebiederm](#) on Wed, 13 Dec 2006 11:07:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

Now that I have changed all of the users remove the old version of these functions. This should be a clear hint to any out of tree users that they should use do_each_pid_task and while_each_pid_task for new code.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

include/linux/pid.h | 14 -----

1 files changed, 0 insertions(+), 14 deletions(-)

diff --git a/include/linux/pid.h b/include/linux/pid.h

index 4dec047..2ac27f9 100644

--- a/include/linux/pid.h

+++ b/include/linux/pid.h

```
@@ -105,20 +105,6 @@ static inline pid_t pid_nr(struct pid *pid)
    return nr;
}
```

-

```
-#define do_each_task_pid(who, type, task) \
```

```
- do { \
```

```
- struct hlist_node *pos___; \
```

```
- struct pid *pid___ = find_pid(who); \
```

```
- if (pid___ != NULL) \
```

```
- hlist_for_each_entry_rcu((task), pos___, \
```

```
- &pid___->tasks[type], pids[type].node) {
```

-

```
-#define while_each_task_pid(who, type, task) \
```

```
- } \
```

```
- } while (0)
```

-

-

```
#define do_each_pid_task(pid, type, task) \
```

```
do { \
```

```
struct hlist_node *pos___; \
```

--

1.4.4.1.g278f

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
