
Subject: Re: [PATCH] usbatm: Update to use the kthread api.
Posted by [ebiederm](#) on Wed, 13 Dec 2006 19:11:01 GMT
[View Forum Message](#) <> [Reply to Message](#)

Cedric Le Goater <clg@fr.ibm.com> writes:

> Eric W. Biederman wrote:
>> During driver initialization if the driver has an expensive
>> initialization routine usbatm starts a separate kernel thread for it.
>>
>> In the driver cleanup routine the code waits to ensure the
>> initialization routine has finished.
>>
>> Switching to the kthread api allowed some of the thread management
>> code to be removed.
>>
>> In addition the kill_proc(SIGTERM, ...) in usbatm_usb_disconnect was
>> removed because it was absolutely pointless. The kernel thread did
>> not handle SIGTERM or any pending signals, so despite marking the
>> signal as pending it would never have been handled.
>
> are you sure that the heavy_init() routines don't handle pending
> signals. they do firmware loading, etc. ?

Well I just took a quick look through them to be certain
and I don't see anything that would. Even inside of the guts of
request firmware. So I'm pretty certain that SIGTERM was something
originally copied from another kernel_thread implementation and
wound up being dead code.

Eric

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
