
Subject: [PATCH 1/59] sysctl x25: Remove unnecessary insert_at_head from register_sysctl_table.

Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:06 GMT

[View Forum Message](#) <> [Reply to Message](#)

Since x25 uses unique binary numbers inserting yourself at the head of the search list for sysctls so you can override already registered sysctls is pointless.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

net/x25/sysctl_net_x25.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/net/x25/sysctl_net_x25.c b/net/x25/sysctl_net_x25.c

index aabda59..94aff67 100644

--- a/net/x25/sysctl_net_x25.c

+++ b/net/x25/sysctl_net_x25.c

@@ -98,7 +98,7 @@ static struct ctl_table x25_root_table[] = {

void __init x25_register_sysctl(void)

{
- x25_table_header = register_sysctl_table(x25_root_table, 1);
+ x25_table_header = register_sysctl_table(x25_root_table, 0);
}

void x25_unregister_sysctl(void)

--

1.4.4.1.g278f

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
