
Subject: [PATCH 4/59] sysctl: sunrpc Don't unnecessarily set ctl_table->de
Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

We don't need this to prevent module unload races so remove the unnecessary code.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

```
net/sunrpc/sysctl.c | 8 +-----
```

```
net/sunrpc/xprtsock.c | 7 +-----
```

```
2 files changed, 2 insertions(+), 13 deletions(-)
```

```
diff --git a/net/sunrpc/sysctl.c b/net/sunrpc/sysctl.c
```

```
index 3852689..6a82ed2 100644
```

```
--- a/net/sunrpc/sysctl.c
```

```
+++ b/net/sunrpc/sysctl.c
```

```
@@ -35,14 +35,8 @@ static ctl_table sunrpc_table[];
```

```
void
```

```
rpc_register_sysctl(void)
```

```
{
```

```
- if (!sunrpc_table_header) {
```

```
+ if (!sunrpc_table_header)
```

```
    sunrpc_table_header = register_sysctl_table(sunrpc_table, 0);
```

```
+#ifdef CONFIG_PROC_FS
```

```
- if (sunrpc_table[0].de)
```

```
- sunrpc_table[0].de->owner = THIS_MODULE;
```

```
+#endif
```

```
- }
```

```
-
```

```
}
```

```
void
```

```
diff --git a/net/sunrpc/xprtsock.c b/net/sunrpc/xprtsock.c
```

```
index 98d1af9..51964cf 100644
```

```
--- a/net/sunrpc/xprtsock.c
```

```
+++ b/net/sunrpc/xprtsock.c
```

```
@@ -1629,13 +1629,8 @@ struct rpc_xprt *xs_setup_tcp(struct sockaddr *addr, size_t addrlen,
```

```
struct rpc_
```

```
int init_socket_xprt(void)
```

```
{
```

```
#ifdef RPC_DEBUG
```

```
- if (!sunrpc_table_header) {
```

```
+ if (!sunrpc_table_header)
```

```
    sunrpc_table_header = register_sysctl_table(sunrpc_table, 0);
```

```
+#ifdef CONFIG_PROC_FS
```

```
- if (sunrpc_table[0].de)
- sunrpc_table[0].de->owner = THIS_MODULE;
-#endif
- }
#endif
```

```
return 0;
```

```
--
```

```
1.4.4.1.g278f
```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
