

---

Subject: [PATCH 5/59] sysctl: rose remove unnecessary insert\_at\_head flag

Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:10 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

From: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)> - unquoted

The sysctl numbers used are unique so setting the insert\_at\_head flag serves no semantic purpose.

Signed-off-by: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)>

---

```
net/rose/sysctl_net_rose.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)
```

```
diff --git a/net/rose/sysctl_net_rose.c b/net/rose/sysctl_net_rose.c
```

```
index 8548c7c..0190a07 100644
```

```
--- a/net/rose/sysctl_net_rose.c
```

```
+++ b/net/rose/sysctl_net_rose.c
```

```
@@ -160,7 +160,7 @@ static ctl_table rose_root_table[] = {
```

```
void __init rose_register_sysctl(void)
```

```
{
- rose_table_header = register_sysctl_table(rose_root_table, 1);
+ rose_table_header = register_sysctl_table(rose_root_table, 0);
}
```

```
void rose_unregister_sysctl(void)
```

```
--
```

```
1.4.4.1.g278f
```

---

Containers mailing list

[Containers@lists.osdl.org](mailto:Containers@lists.osdl.org)

<https://lists.osdl.org/mailman/listinfo/containers>

---