Subject: [PATCH 7/59] sysctl: llc remove unnecessary insert_at_head flag
Posted by ebiederm on Tue, 16 Jan 2007 16:39:12 GMT
View Forum Message <> Reply to Message

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

The sysctl numbers used are unique so setting the insert_at_head
flag serves no semantis purpose, and is just confusing.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>
---
 net/llc/sysctl_net_llc.c | 2 +-
 1 files changed, 1 insertions(+), 1 deletions(-)

```
diff --git a/net/llc/sysctl_net_llc.c b/net/llc/sysctl_net_llc.c
index 45d7dd9..4aab676 100644
--- a/net/llc/sysctl_net_llc.c
+++ b/net/llc/sysctl_net_llc.c
@@ -116,7 +116,7 @@ static struct ctl_table_header *llc_table_header;

 int __init llc_sysctl_init(void)
 {
- llc_table_header = register_sysctl_table(llc_root_table, 1);
+ llc_table_header = register_sysctl_table(llc_root_table, 0);

  return llc_table_header ? 0 : -ENOMEM;
 }
```
--
1.4.4.1.g278f

_____
Containers mailing list
Containers@lists.osdl.org
https://lists.osdl.org/mailman/listinfo/containers