
Subject: [PATCH 8/59] sysctl: ipx remove unnecessary insert_at_head flag

Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

The sysctl numbers used are unique so setting the insert_at_head flag serves no semantic purpose and is just confusing.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

net/ipx/sysctl_net_ipx.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/net/ipx/sysctl_net_ipx.c b/net/ipx/sysctl_net_ipx.c

index fa57473..0442f44 100644

--- a/net/ipx/sysctl_net_ipx.c

+++ b/net/ipx/sysctl_net_ipx.c

@@ -52,7 +52,7 @@ static struct ctl_table_header *ipx_table_header;

void ipx_register_sysctl(void)

```
{  
- ipx_table_header = register_sysctl_table(ipx_root_table, 1);  
+ ipx_table_header = register_sysctl_table(ipx_root_table, 0);  
}
```

void ipx_unregister_sysctl(void)

--

1.4.4.1.g278f

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
