
Subject: [PATCH 16/59] sysctl: md Remove unnecessary insert_at_head flag

Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

The sysctls used by the md driver are have unique binary numbers so remove the insert_at_head flag as it serves no useful purpose.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

drivers/md/md.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/drivers/md/md.c b/drivers/md/md.c

index d1cb45f..966e8be 100644

--- a/drivers/md/md.c

+++ b/drivers/md/md.c

@@ -5551,7 +5551,7 @@ static int __init md_init(void)
md_probe, NULL, NULL);

register_reboot_notifier(&md_notifier);
- raid_table_header = register_sysctl_table(raid_root_table, 1);
+ raid_table_header = register_sysctl_table(raid_root_table, 0);

md_geninit();
return (0);

--

1.4.4.1.g278f

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
