

---

Subject: [PATCH 17/59] sysctl: mac\_hid remove unnecessary insert\_at\_head flag  
Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

From: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)> - unquoted

With unique sysctl binary numbers setting insert\_at\_head is pointless.

Signed-off-by: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)>

---

```
drivers/macintosh/mac_hid.c | 2 +-  
1 files changed, 1 insertions(+), 1 deletions(-)
```

```
diff --git a/drivers/macintosh/mac_hid.c b/drivers/macintosh/mac_hid.c
```

```
index ee6b4ca..c676740 100644
```

```
--- a/drivers/macintosh/mac_hid.c
```

```
+++ b/drivers/macintosh/mac_hid.c
```

```
@@ -138,7 +138,7 @@ int __init mac_hid_init(void)
```

```
    return err;
```

```
    #if defined(CONFIG_SYSCTL)
```

```
    - mac_hid_sysctl_header = register_sysctl_table(mac_hid_root_dir, 1);
```

```
    + mac_hid_sysctl_header = register_sysctl_table(mac_hid_root_dir, 0);
```

```
    #endif /* CONFIG_SYSCTL */
```

```
    return 0;
```

```
--
```

```
1.4.4.1.g278f
```

---

Containers mailing list

[Containers@lists.osdl.org](mailto:Containers@lists.osdl.org)

<https://lists.osdl.org/mailman/listinfo/containers>

---