
Subject: [PATCH 18/59] sysctl: ipmi remove unnecessary insert_at_head flag
Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

With unique sysctl binary numbers setting insert_at_head is pointless.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

drivers/char/ipmi/ipmi_poweroff.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/drivers/char/ipmi/ipmi_poweroff.c b/drivers/char/ipmi/ipmi_poweroff.c
index 9d23136..b3ae65e 100644

--- a/drivers/char/ipmi/ipmi_poweroff.c

+++ b/drivers/char/ipmi/ipmi_poweroff.c

@@ -686,7 +686,7 @@ static int ipmi_poweroff_init (void)
 printk(KERN_INFO PFX "Power cycle is enabled.\n");

#ifdef CONFIG_PROC_FS

- ipmi_table_header = register_sysctl_table(ipmi_root_table, 1);

+ ipmi_table_header = register_sysctl_table(ipmi_root_table, 0);

if (!ipmi_table_header) {

printk(KERN_ERR PFX "Unable to register powercycle sysctl\n");
 rv = -ENOMEM;

--

1.4.4.1.g278f

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
