
Subject: [PATCH 19/59] sysctl: cdrom remove unnecessary insert_at_head flag
Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:24 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

With unique binary sysctl numbers setting insert_at_head to override other sysctl entries is pointless.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

drivers/cdrom/cdrom.c | 2 +-
1 files changed, 1 insertions(+), 1 deletions(-)

diff --git a/drivers/cdrom/cdrom.c b/drivers/cdrom/cdrom.c

index 3105ddd..f0a6801 100644

--- a/drivers/cdrom/cdrom.c

+++ b/drivers/cdrom/cdrom.c

```
@@ -3553,7 +3553,7 @@ static void cdrom_sysctl_register(void)
    if (initialized == 1)
        return;
```

```
- cdrom_sysctl_header = register_sysctl_table(cdrom_root_table, 1);
+ cdrom_sysctl_header = register_sysctl_table(cdrom_root_table, 0);
    if (cdrom_root_table->ctl_name && cdrom_root_table->child->de)
        cdrom_root_table->child->de->owner = THIS_MODULE;
```

--

1.4.4.1.g278f

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
