Subject: [PATCH 34/59] sysctl: s390 Remove unnecessary use of insert_at_head
Posted by ebiederm on Tue, 16 Jan 2007 16:39:39 GMT
View Forum Message <> Reply to Message

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>
---
 arch/s390/appldata/appldata_base.c | 4 ++--
 arch/s390/kernel/debug.c | 2 +-
 arch/s390/mm/cmm.c | 2 +-
 3 files changed, 4 insertions(+), 4 deletions(-)

```
diff --git a/arch/s390/appldata/appldata_base.c b/arch/s390/appldata/appldata_base.c
index b8c2372..cdc4109 100644
--- a/arch/s390/appldata/appldata_base.c
+++ b/arch/s390/appldata/appldata_base.c
@@ -506,7 +506,7 @@ int appldata_register_ops(struct appldata_ops *ops)

  ops->ctl_table[3].ctl_name = 0;

- ops->sysctl_header = register_sysctl_table(ops->ctl_table,1);
+ ops->sysctl_header = register_sysctl_table(ops->ctl_table,0);

  P_INFO("%s-ops registered!\n", ops->name);
  return 0;
@@ -606,7 +606,7 @@ static int __init appldata_init(void)
  /* Register cpu hotplug notifier */
  register_hotcpu_notifier(&appldata_nb);

- appldata_sysctl_header = register_sysctl_table(appldata_dir_table, 1);
+ appldata_sysctl_header = register_sysctl_table(appldata_dir_table, 0);
 #ifdef MODULE
  appldata_dir_table[0].de->owner = THIS_MODULE;
  appldata_table[0].de->owner = THIS_MODULE;
diff --git a/arch/s390/kernel/debug.c b/arch/s390/kernel/debug.c
index c81f8e5..d38cb27 100644
--- a/arch/s390/kernel/debug.c
+++ b/arch/s390/kernel/debug.c
@@ -1053,7 +1053,7 @@ __init debug_init(void)
 {
  int rc = 0;

- s390dbf_sysctl_header = register_sysctl_table(s390dbf_dir_table, 1);
+ s390dbf_sysctl_header = register_sysctl_table(s390dbf_dir_table, 0);
  down(&debug_lock);
  debug_debugfs_root_entry = debugfs_create_dir(DEBUG_DIR_ROOT,NULL);
  printk(KERN_INFO "debug: Initialization complete\n");
```

```
diff --git a/arch/s390/mm/cmm.c b/arch/s390/mm/cmm.c
index df733d5..5f83a3f 100644
--- a/arch/s390/mm/cmm.c
+++ b/arch/s390/mm/cmm.c
@@ -418,7 +418,7 @@ cmm_init (void)
  int rc = -ENOMEM;

 #ifdef CONFIG_CMM_PROC
- cmm_sysctl_header = register_sysctl_table(cmm_dir_table, 1);
+ cmm_sysctl_header = register_sysctl_table(cmm_dir_table, 0);
  if (!cmm_sysctl_header)
   goto out;
 #endif
--
1.4.4.1.g278f
```

_____

Containers mailing list
Containers@lists.osdl.org
https://lists.osdl.org/mailman/listinfo/containers