
Subject: [PATCH 34/59] sysctl: s390 Remove unnecessary use of insert_at_head
Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:39 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

arch/s390/appldata/appldata_base.c | 4 ++--
arch/s390/kernel/debug.c | 2 +-
arch/s390/mm/cmm.c | 2 +-
3 files changed, 4 insertions(+), 4 deletions(-)

diff --git a/arch/s390/appldata/appldata_base.c b/arch/s390/appldata/appldata_base.c
index b8c2372..cdc4109 100644

--- a/arch/s390/appldata/appldata_base.c
+++ b/arch/s390/appldata/appldata_base.c
@@ -506,7 +506,7 @@ int appldata_register_ops(struct appldata_ops *ops)

ops->ctl_table[3].ctl_name = 0;

- ops->sysctl_header = register_sysctl_table(ops->ctl_table,1);
+ ops->sysctl_header = register_sysctl_table(ops->ctl_table,0);

P_INFO("%s-ops registered!\n", ops->name);
return 0;
@@ -606,7 +606,7 @@ static int __init appldata_init(void)
/* Register cpu hotplug notifier */
register_hotcpu_notifier(&appldata_nb);

- appldata_sysctl_header = register_sysctl_table(appldata_dir_table, 1);
+ appldata_sysctl_header = register_sysctl_table(appldata_dir_table, 0);
#ifdef MODULE

appldata_dir_table[0].de->owner = THIS_MODULE;
appldata_table[0].de->owner = THIS_MODULE;
diff --git a/arch/s390/kernel/debug.c b/arch/s390/kernel/debug.c
index c81f8e5..d38cb27 100644

--- a/arch/s390/kernel/debug.c
+++ b/arch/s390/kernel/debug.c
@@ -1053,7 +1053,7 @@ __init debug_init(void)
{
int rc = 0;

- s390dbf_sysctl_header = register_sysctl_table(s390dbf_dir_table, 1);
+ s390dbf_sysctl_header = register_sysctl_table(s390dbf_dir_table, 0);
down(&debug_lock);
debug_debugfs_root_entry = debugfs_create_dir(DEBUG_DIR_ROOT, NULL);
printk(KERN_INFO "debug: Initialization complete\n");

```
diff --git a/arch/s390/mm/cmm.c b/arch/s390/mm/cmm.c
index df733d5..5f83a3f 100644
--- a/arch/s390/mm/cmm.c
+++ b/arch/s390/mm/cmm.c
@@ -418,7 +418,7 @@ cmm_init (void)
     int rc = -ENOMEM;

#ifdef CONFIG_CMM_PROC
- cmm_sysctl_header = register_sysctl_table(cmm_dir_table, 1);
+ cmm_sysctl_header = register_sysctl_table(cmm_dir_table, 0);
     if (!cmm_sysctl_header)
         goto out;
#endif
--
1.4.4.1.g278f
```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
