
Subject: [PATCH 36/59] sysctl: C99 convert ctl_tables entries in arch/ppc/kernel/ppc_htab.c

Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

And make the mode of the kernel directory 0555 no one is allowed to write to sysctl directories.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

arch/ppc/kernel/ppc_htab.c | 11 ++++++---

1 files changed, 8 insertions(+), 3 deletions(-)

diff --git a/arch/ppc/kernel/ppc_htab.c b/arch/ppc/kernel/ppc_htab.c

index bd129d3..77b20ff 100644

--- a/arch/ppc/kernel/ppc_htab.c

+++ b/arch/ppc/kernel/ppc_htab.c

@@ -442,11 +442,16 @@ static ctl_table htab_ctl_table[]={

 .mode = 0644,

 .proc_handler = &proc_dol2crvec,

 },

- { 0, },

+ {}

};

static ctl_table htab_sysctl_root[] = {

- { 1, "kernel", NULL, 0, 0755, htab_ctl_table, },

- { 0, },

+ {

+ .ctl_name = CTL_KERN,

+ .procname = "kernel",

+ .mode = 0555,

+ .child = htab_ctl_table,

+ },

+ {}

};

static int __init

--

1.4.4.1.g278f

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
