
Subject: [PATCH 38/59] sysctl: x86_64 Remove unnecessary use of insert_at_head
Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:43 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

The only sysctl x86_64 provides are not provided elsewhere,
so insert_at_head is unnecessary.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

```
arch/x86_64/ia32/ia32_binfmt.c | 2 +-  
arch/x86_64/mm/init.c          | 2 +-  
2 files changed, 2 insertions(+), 2 deletions(-)
```

```
diff --git a/arch/x86_64/ia32/ia32_binfmt.c b/arch/x86_64/ia32/ia32_binfmt.c  
index 543ef4f..75677ad 100644
```

```
--- a/arch/x86_64/ia32/ia32_binfmt.c  
+++ b/arch/x86_64/ia32/ia32_binfmt.c  
@@ -408,7 +408,7 @@ static ctl_table abi_root_table2[] = {
```

```
static __init int ia32_binfmt_init(void)  
{  
- register_sysctl_table(abi_root_table2, 1);  
+ register_sysctl_table(abi_root_table2, 0);  
    return 0;  
}  
__initcall(ia32_binfmt_init);
```

```
diff --git a/arch/x86_64/mm/init.c b/arch/x86_64/mm/init.c  
index 2968b90..65aa66c 100644
```

```
--- a/arch/x86_64/mm/init.c  
+++ b/arch/x86_64/mm/init.c  
@@ -724,7 +724,7 @@ static ctl_table debug_root_table2[] = {
```

```
static __init int x8664_sysctl_init(void)  
{  
- register_sysctl_table(debug_root_table2, 1);  
+ register_sysctl_table(debug_root_table2, 0);  
    return 0;  
}  
__initcall(x8664_sysctl_init);
```

--

1.4.4.1.g278f

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
