
Subject: [PATCH 39/59] sysctl: C99 convert ctl_tables in
arch/x86_64/ia32/ia32_binfmt.c

Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

arch/x86_64/ia32/ia32_binfmt.c | 30 ++++++-----

1 files changed, 20 insertions(+), 10 deletions(-)

diff --git a/arch/x86_64/ia32/ia32_binfmt.c b/arch/x86_64/ia32/ia32_binfmt.c

index 75677ad..644b203 100644

--- a/arch/x86_64/ia32/ia32_binfmt.c

+++ b/arch/x86_64/ia32/ia32_binfmt.c

@@ -395,16 +395,26 @@ EXPORT_SYMBOL(ia32_setup_arg_pages);

#include <linux/sysctl.h>

static ctl_table abi_table2[] = {

- { 99, "vsyscall32", &sysctl_vsyscall32, sizeof(int), 0644, NULL,

- proc_dointvec },

- { 0, }

-};

-

-static ctl_table abi_root_table2[] = {

- { .ctl_name = CTL_ABI, .procname = "abi", .mode = 0555,

- .child = abi_table2 },

- { 0 },

-};

+ {

+ .ctl_name = 99,

+ .procname = "vsyscall32",

+ .data = &sysctl_vsyscall32,

+ .maxlen = sizeof(int),

+ .mode = 0644,

+ .proc_handler = proc_dointvec

+ },

+ {}

+};

+

+static ctl_table abi_root_table2[] = {

+ {

+ .ctl_name = CTL_ABI,

+ .procname = "abi",

+ .mode = 0555,

+ .child = abi_table2

+ },

```
+ {}
```

```
+};
```

```
static __init int ia32_binfmt_init(void)
```

```
{
```

```
--
```

```
1.4.4.1.g278f
```

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
