
Subject: [PATCH 39/59] sysctl: C99 convert ctl_tables in

arch/x86_64/ia32/ia32_binfmt.c

Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

arch/x86_64/ia32/ia32_binfmt.c | 30 ++++++-----
1 files changed, 20 insertions(+), 10 deletions(-)

```
diff --git a/arch/x86_64/ia32/ia32_binfmt.c b/arch/x86_64/ia32/ia32_binfmt.c
index 75677ad..644b203 100644
--- a/arch/x86_64/ia32/ia32_binfmt.c
+++ b/arch/x86_64/ia32/ia32_binfmt.c
@@ -395,16 +395,26 @@ EXPORT_SYMBOL(ia32_setup_arg_pages);
#include <linux/sysctl.h>

static ctl_table abi_table2[] = {
- { 99, "vsyscall32", &sysctl_vsyscall32, sizeof(int), 0644, NULL,
-   proc_dointvec },
- { 0, }
-};
-
-static ctl_table abi_root_table2[] = {
- { .ctl_name = CTL_ABI, .procname = "abi", .mode = 0555,
-   .child = abi_table2 },
- { 0 },
-};
+ {
+   .ctl_name = 99,
+   .procname = "vsyscall32",
+   .data = &sysctl_vsyscall32,
+   . maxlen = sizeof(int),
+   .mode = 0644,
+   .proc_handler = proc_dointvec
+ },
+ {}
+};
+
+static ctl_table abi_root_table2[] = {
+ {
+   .ctl_name = CTL_ABI,
+   .procname = "abi",
+   .mode = 0555,
+   .child = abi_table2
+ },
```

```
+ {}  
+};  
  
static __init int ia32_binfmt_init(void)  
{  
--  
1.4.4.1.g278f
```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
