
Subject: [PATCH 54/59] sysctl: Remove support for directory strategy routines.

Posted by [ebiederm](#) on Tue, 16 Jan 2007 16:39:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

parse_table has support for calling a strategy routine when descending into a directory. To date no one has used this functionality and the /proc/sys interface has no analog to it.

So no one is using this functionality kill it and make the binary sysctl code easier to follow.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

kernel/sysctl.c | 8 -----

1 files changed, 0 insertions(+), 8 deletions(-)

diff --git a/kernel/sysctl.c b/kernel/sysctl.c

index e655b11..2c3703d 100644

--- a/kernel/sysctl.c

+++ b/kernel/sysctl.c

@@ -1171,14 +1171,6 @@ repeat:

```
    if (table->child) {
        if (ctl_perm(table, 001))
            return -EPERM;
-   if (table->strategy) {
-       error = table->strategy(
-           table, name, nlen,
-           oldval, oldlenp,
-           newval, newlen);
-       if (error)
-           return error;
-   }
    name++;
    nlen--;
    table = table->child;
```

--

1.4.4.1.g278f

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
