
Subject: Re: [PATCH 45/59] sysctl: C99 convert ctl_tables in
drivers/parport/procfs.c

Posted by [ebiederm](#) on Tue, 16 Jan 2007 23:00:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

Ingo Oeser <ioe-lkml@ramera.de> writes:

> Hi Eric,

>

> On Tuesday, 16. January 2007 17:39, Eric W. Biederman wrote:

>> diff --git a/drivers/parport/procfs.c b/drivers/parport/procfs.c

>> index 2e744a2..5337789 100644

>> --- a/drivers/parport/procfs.c

>> +++ b/drivers/parport/procfs.c

>> @@ -263,50 +263,118 @@ struct parport_sysctl_table {

>> + {

>> + .ctl_name = DEV_PARPORT_BASE_ADDR,

>> + .procname = "base-addr",

>> + .data = NULL,

>> + .maxlen = 0,

>> + .mode = 0444,

>> + .proc_handler = &do_hardware_base_addr

>> + },

>

> No need to initialize to zero or NULL. Just list any variable, which is NOT zero
> or NULL.

Agreed. In this case it was left for clarity.

>> + {

>> + .ctl_name = DEV_PARPORT_AUTOPROBE + 1,

>> + .procname = "autoprobe0",

>> + .data = NULL,

>> + .maxlen = 0,

>> + .maxlen = 0444,

>> + .proc_handler = &do_autoprobe

>> + },

>

> Typo here? .mode = 0444 makes mor sense.

Yep looks like it. On my todo.

Eric

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
