
Subject: Re: [PATCH 18/59] sysctl: ipmi remove unnecessary insert_at_head flag
Posted by [Benjamin Herrenschmidt](#) on Wed, 17 Jan 2007 03:14:54 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Tue, 2007-01-16 at 09:39 -0700, Eric W. Biederman wrote:

> From: Eric W. Biederman <ebiederm@xmission.com> - unquoted
>
> With unique sysctl binary numbers setting insert_at_head is pointless.
>
> Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

Acked-by: Benjamin Herrenschmidt <benh@kernel.crashing.org>

> ---
> drivers/char/ipmi/ipmi_poweroff.c | 2 +-
> 1 files changed, 1 insertions(+), 1 deletions(-)
>
> diff --git a/drivers/char/ipmi/ipmi_poweroff.c b/drivers/char/ipmi/ipmi_poweroff.c
> index 9d23136..b3ae65e 100644
> --- a/drivers/char/ipmi/ipmi_poweroff.c
> +++ b/drivers/char/ipmi/ipmi_poweroff.c
> @@ -686,7 +686,7 @@ static int ipmi_poweroff_init (void)
> printk(KERN_INFO PFX "Power cycle is enabled.\n");
>
> #ifdef CONFIG_PROC_FS
> - ipmi_table_header = register_sysctl_table(ipmi_root_table, 1);
> + ipmi_table_header = register_sysctl_table(ipmi_root_table, 0);
> if (ipmi_table_header) {
> printk(KERN_ERR PFX "Unable to register powercycle sysctl\n");
> rv = -ENOMEM;

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
