
Subject: Re: [PATCH 25/59] sysctl: C99 convert arch/frv/kernel/pm.c

Posted by [dev](#) on Wed, 17 Jan 2007 17:14:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

another small minor note.

> From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

>

> Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

> ---

> arch/frv/kernel/pm.c | 50 ++++++-----

> 1 files changed, 43 insertions(+), 7 deletions(-)

>

> diff --git a/arch/frv/kernel/pm.c b/arch/frv/kernel/pm.c

> index c1840d6..aa50333 100644

> --- a/arch/frv/kernel/pm.c

> +++ b/arch/frv/kernel/pm.c

> @@ -401,17 +401,53 @@ static int cm_sysctl(ctl_table *table, int __user *name, int nlen,

>

> static struct ctl_table pm_table[] =

> {

> - {CTL_PM_SUSPEND, "suspend", NULL, 0, 0200, NULL, &sysctl_pm_do_suspend},

> - {CTL_PM_CMODE, "cmode", &clock_cmode_current, sizeof(int), 0644, NULL,

> &cmode_procctl, &cmode_sysctl, NULL},

> - {CTL_PM_P0, "p0", &clock_p0_current, sizeof(int), 0644, NULL, &p0_procctl, &p0_sysctl,

> NULL},

> - {0}

> + {

> + .ctl_name = CTL_PM_SUSPEND,

> + .procname = "suspend",

> + .data = NULL,

> + .maxlen = 0,

> + .mode = 0200,

> + .proc_handler = &sysctl_pm_do_suspend,

> + },

> + {

> + .ctl_name = CTL_PM_CMODE,

> + .procname = "cmode",

> + .data = &clock_cmode_current,

> + .maxlen = sizeof(int),

> + .mode = 0644,

> + .proc_handler = &cmode_procctl,

> + .strategy = &cmode_sysctl,

> + },

> + {

> + .ctl_name = CTL_PM_P0,

```

> + .procname = "p0",
> + .data = &clock_p0_current,
> + .maxlen = sizeof(int),
> + .mode = 0644,
> + .proc_handler = &p0_procctl,
> + .strategy = &p0_sysctl,
> + },
> + {
> + .ctl_name = CTL_PM_CM,
> + .procname = "cm",
> + .data = &clock_cm_current,
> + .maxlen = sizeof(int),
> + .mode = 0644,
> + .proc_handler = &cm_procctl,
> + .strategy = &cm_sysctl,
> + },
> + { .ctl_name = 0}
in next patch (26/59) you write just "{ }". .ctl_name = 0 not required here.

```

```

> };
>
> static struct ctl_table pm_dir_table[] =
> {
> - {CTL_PM, "pm", NULL, 0, 0555, pm_table},
> - {0}
> + {
> + .ctl_name = CTL_PM,
> + .procname = "pm",
> + .mode = 0555,
> + .child = pm_table,
> + },
> + { .ctl_name = 0}
> };
>
> /*

```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
