
Subject: [patch 02/12] net namespace : store L2 parent namespace

Posted by [Daniel Lezcano](#) on Fri, 19 Jan 2007 15:47:16 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Daniel Lezcano <dlezcano@fr.ibm.com>

All L3 namespaces are the final nodes of the L2 namespaces tree. Because their share some ressources coming from the L2 namespace. The L2 parent namespace should be stored into the L3 child when it is created.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

```
include/linux/net_namespace.h |  1 +
net/core/net_namespace.c    | 11 ++++++++
2 files changed, 12 insertions(+)
```

Index: 2.6.20-rc4-mm1/include/linux/net_namespace.h

```
=====
--- 2.6.20-rc4-mm1.orig/include/linux/net_namespace.h
+++ 2.6.20-rc4-mm1/include/linux/net_namespace.h
@@ -27,6 +27,7 @@
#define NET_NS_LEVEL2 1
#define NET_NS_LEVEL3 2
 unsigned int level;
+ struct net_namespace *parent;
};
```

```
extern struct net_namespace init_net_ns;
```

Index: 2.6.20-rc4-mm1/net/core/net_namespace.c

```
=====
--- 2.6.20-rc4-mm1.orig/net/core/net_namespace.c
+++ 2.6.20-rc4-mm1/net/core/net_namespace.c
@@ -22,6 +22,7 @@
 .loopback_dev_p = NULL,
 .pcpu_lstats_p = NULL,
 .level      = NET_NS_LEVEL2,
+ .parent     = NULL,
};
```

```
#ifdef CONFIG_NET_NS
@@ -62,6 +63,12 @@
 if (ip_fib_struct_init())
 goto out_fib4;
}
+
+ if (level == NET_NS_LEVEL3) {
```

```
+ get_net_ns(old_ns);
+ ns->parent = old_ns;
+
+ ns->level = level;
if (loopback_init())
    goto out_loopback;
@@ -126,8 +133,12 @@
    ns, atomic_read(&ns->kref.refcount));
return;
}
+
if (ns->level == NET_NS_LEVEL2)
    ip_fib_struct_cleanup(ns);
+ if (ns->level == NET_NS_LEVEL3)
+ put_net_ns(ns->parent);
+
printk(KERN_DEBUG "NET_NS: net namespace %p destroyed\n", ns);
kfree(ns);
}
```

--

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
