
Subject: [RFC][PATCH 2/4] remove proc_mnt's use or killing inodes

Posted by [Dave Hansen](#) on Fri, 26 Jan 2007 22:42:10 GMT

[View Forum Message](#) <> [Reply to Message](#)

We use proc_mnt as a shortcut to find a superblock on which to go killing /proc inodes. This will break if we ever have more than one /proc superblock. So, use the superblock list to go find each of the /proc sb's and kill inodes on each superblock.

This eliminates one more use of proc_mnt.

lxc-dave/fs/proc/generic.c | 28 ++++++-----
1 file changed, 23 insertions(+), 5 deletions(-)

```
diff -puN fs/proc/generic.c~A1-remove-proc_mnt-0 fs/proc/generic.c
--- lxc/fs/proc/generic.c~A1-remove-proc_mnt-0 2007-01-26 14:29:17.000000000 -0800
+++ lxc-dave/fs/proc/generic.c 2007-01-26 14:29:17.000000000 -0800
@@ -547,13 +547,10 @@ static int proc_register(struct proc_dir
     return 0;
 }
```

```
-/*
- * Kill an inode that got unregistered..
- */
-static void proc_kill_inodes(struct proc_dir_entry *de)
+static void proc_kill_inodes_sb(struct proc_dir_entry *de,
+ struct super_block *sb)
{
    struct list_head *p;
- struct super_block *sb = proc_mnt->mnt_sb;
```

```
/*
 * Actually it's a partial revoke().
@@ -577,6 +574,27 @@ static void proc_kill_inodes(struct proc
    file_list_unlock();
 }
```

```
+/*
+ * Kill an inode that got unregistered..
+ */
+static void proc_kill_inodes(struct proc_dir_entry *de)
+{
+ struct list_head *l;
+ struct file_system_type *procfs;
+ }
```

```
+ procfs = get_fs_type("proc");
+ if (!procfs)
+ return;
+
+ spin_lock(&sb_lock);
+ list_for_each(l, &procfs->fs_supers) {
+ struct super_block *sb;
+ sb = list_entry(l, struct super_block, s_instances);
+ proc_kill_inodes_sb(de, sb);
+ }
+ spin_unlock(&sb_lock);
+}
+
static struct proc_dir_entry *proc_create(struct proc_dir_entry **parent,
    const char *name,
    mode_t mode,
```

—

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
