

---

Subject: Re: [PATCH 49/59] sysctl: Move init\_irq\_proc into init/main where it belongs

Posted by [Andrew Morton](#) on Sat, 27 Jan 2007 10:51:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On Tue, 16 Jan 2007 09:39:54 -0700

"Eric W. Biederman" <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)> wrote:

> From: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)> - unquoted

>

> Signed-off-by: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)>

> ---

> init/main.c | 3 +++

> kernel/sysctl.c | 3 ---

> 2 files changed, 3 insertions(+), 3 deletions(-)

>

> diff --git a/init/main.c b/init/main.c

> index 8b4a7d7..8af5c6e 100644

> --- a/init/main.c

> +++ b/init/main.c

> @@ -691,6 +691,9 @@ static void \_\_init do\_basic\_setup(void)

> #ifdef CONFIG\_SYSCTL

> sysctl\_init();

> #endif

> +#ifdef CONFIG\_PROC\_FS

> + init\_irq\_proc();

> +#endif

>

> do\_initcalls();

> }

> diff --git a/kernel/sysctl.c b/kernel/sysctl.c

> index 600b333..7420761 100644

> --- a/kernel/sysctl.c

> +++ b/kernel/sysctl.c

> @@ -1172,8 +1172,6 @@ static ctl\_table dev\_table[] = {

> { .ctl\_name = 0 }

> };

>

> -extern void init\_irq\_proc (void);

> -

> static DEFINE\_SPINLOCK(sysctl\_lock);

>

> /\* called under sysctl\_lock \*/

> @@ -1219,7 +1217,6 @@ void \_\_init sysctl\_init(void)

> {

> #ifdef CONFIG\_PROC\_SYSCTL

> register\_proc\_table(root\_table, proc\_sys\_root, &root\_table\_header);

> - init\_irq\_proc();

```
> #endif  
> }
```

sparc64:

init/main.c: In function `do\_basic\_setup':

init/main.c:707: warning: implicit declaration of function `init\_irq\_proc'

I couldn't be bothered working out how init/main.c is supposed to get at its declaration of init\_irq\_proc(). It's not allowed to include linux/irq.h.

---

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>

---