
Subject: Re: [PATCH 49/59] sysctl: Move init_irq_proc into init/main where it belongs

Posted by [Andrew Morton](#) on Sat, 27 Jan 2007 10:51:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Tue, 16 Jan 2007 09:39:54 -0700

"Eric W. Biederman" <ebiederm@xmission.com> wrote:

> From: Eric W. Biederman <ebiederm@xmission.com> - unquoted

>

> Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

> ---

> init/main.c | 3 +++

> kernel/sysctl.c | 3 ---

> 2 files changed, 3 insertions(+), 3 deletions(-)

>

> diff --git a/init/main.c b/init/main.c

> index 8b4a7d7..8af5c6e 100644

> --- a/init/main.c

> +++ b/init/main.c

> @@ -691,6 +691,9 @@ static void __init do_basic_setup(void)

> #ifdef CONFIG_SYSCTL

> sysctl_init();

> #endif

> +#ifdef CONFIG_PROC_FS

> + init_irq_proc();

> +#endif

>

> do_initcalls();

> }

> diff --git a/kernel/sysctl.c b/kernel/sysctl.c

> index 600b333..7420761 100644

> --- a/kernel/sysctl.c

> +++ b/kernel/sysctl.c

> @@ -1172,8 +1172,6 @@ static ctl_table dev_table[] = {

> { .ctl_name = 0 }

> };

>

> -extern void init_irq_proc (void);

> -

> static DEFINE_SPINLOCK(sysctl_lock);

>

> /* called under sysctl_lock */

> @@ -1219,7 +1217,6 @@ void __init sysctl_init(void)

> {

> #ifdef CONFIG_PROC_SYSCTL

> register_proc_table(root_table, proc_sys_root, &root_table_header);

> - init_irq_proc();

```
> #endif  
> }
```

sparc64:

init/main.c: In function `do_basic_setup':

init/main.c:707: warning: implicit declaration of function `init_irq_proc'

I couldn't be bothered working out how init/main.c is supposed to get at its declaration of init_irq_proc(). It's not allowed to include linux/irq.h.

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
