
Subject: [PATCH] Use task_pgrp() in solaris procids
Posted by [Sukadev Bhattiprolu](#) on Thu, 22 Feb 2007 23:35:30 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [PATCH] Use task_pgrp() in solaris procids

Use task_pgrp() in solaris procids code.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <cclg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: containers@lists.osdl.org

arch/sparc64/solaris/misc.c | 4 +---
1 file changed, 2 insertions(+), 2 deletions(-)

Index: lx26-20-mm1/arch/sparc64/solaris/misc.c

```
=====
--- lx26-20-mm1.orig/arch/sparc64/solaris/misc.c 2007-02-04 10:44:54.000000000 -0800
+++ lx26-20-mm1/arch/sparc64/solaris/misc.c 2007-02-16 15:47:02.000000000 -0800
@@ -413,7 +413,7 @@ asmlinkage int solaris_procids(int cmd,
```

```
switch (cmd) {
    case 0: /* getpgrp */
-        return process_group(current);
+        return pid_nr(task_pgrp(current));
    case 1: /* setpgrp */
    {
        int (*sys_setpgid)(pid_t,pid_t) =
@@ -424,7 +424,7 @@ asmlinkage int solaris_procids(int cmd,
        ret = sys_setpgid(0, 0);
        if (ret) return ret;
        proc_clear_tty(current);
-        return process_group(current);
+        return pid_nr(task_pgrp(current));
    }
    case 2: /* getsid */
    {
```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
