
Subject: [PATCH 2/5] Explicitly set pgid and sid of init process
Posted by [Sukadev Bhattiprolu](#) on Thu, 01 Mar 2007 03:57:24 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [PATCH 2/5] Explicitly set pgid and sid of init process

Explicitly set pgid and sid of init process to 1.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: Eric Biederman <ebiederm@xmission.com>
Cc: Herbert Poetzl <herbert@13thfloor.at>
Cc: <containers@lists.osdl.org>
Signed-off-by: Andrew Morton <akpm@osdl.org>

init/main.c | 1 +
1 file changed, 1 insertion(+)

Index: lx26-20-mm2c/init/main.c

```
=====
--- lx26-20-mm2c.orig/init/main.c 2007-02-28 15:49:13.000000000 -0800
+++ lx26-20-mm2c/init/main.c 2007-02-28 15:49:35.000000000 -0800
@@ -791,6 +791,7 @@ static int __init init(void * unused)
 */
init_pid_ns.child_reaper = current;

+ __set_special_pids(1, 1);
cad_pid = task_pid(current);

smp_prepare_cpus(max_cpus);
```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
