

---

Subject: [PATCH 5/5] Use task\_pgrp() task\_session() in copy\_process()  
Posted by [Sukadev Bhattiprolu](#) on Thu, 01 Mar 2007 03:59:02 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>  
Subject: [PATCH 5/5] Use task\_pgrp() task\_session() in copy\_process().

Use task\_pgrp() and task\_session() in copy\_process(), and  
avoid find\_pid() call when attaching the task to its process  
group and session.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>  
Cc: Cedric Le Goater <clg@fr.ibm.com>  
Cc: Dave Hansen <haveblue@us.ibm.com>  
Cc: Serge Hallyn <serue@us.ibm.com>  
Cc: containers@lists.osdl.org

---  
kernel/fork.c | 9 +++-----  
1 file changed, 3 insertions(+), 6 deletions(-)

Index: lx26-20-mm2c/kernel/fork.c

=====

--- lx26-20-mm2c.orig/kernel/fork.c 2007-02-28 17:29:18.000000000 -0800  
+++ lx26-20-mm2c/kernel/fork.c 2007-02-28 19:23:33.000000000 -0800  
@@ -1253,14 +1253,11 @@ static struct task\_struct \*copy\_process(  
tracehook\_init\_task(p);

```
if (thread_group_leader(p)) {  
- pid_t pgid = process_group(current);  
- pid_t sid = process_session(current);  
-  
p->signal->tty = current->signal->tty;  
- p->signal->pgrp = pgid;  
+ p->signal->pgrp = process_group(current);  
set_signal_session(p->signal, process_session(current));  
- attach_pid(p, PIDTYPE_PGID, find_pid(pgid));  
- attach_pid(p, PIDTYPE_SID, find_pid(sid));  
+ attach_pid(p, PIDTYPE_PGID, task_pgrp(current));  
+ attach_pid(p, PIDTYPE_SID, task_session(current));  
  
list_add_tail_rcu(&p->tasks, &init_task.tasks);  
__get_cpu_var(process_counts)++;
```

---

Containers mailing list  
Containers@lists.osdl.org  
<https://lists.osdl.org/mailman/listinfo/containers>

---