
Subject: [PATCH] Kill unused sesssion and group values in rocket driver
Posted by [Sukadev Bhattiprolu](#) on Tue, 13 Mar 2007 04:49:33 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [PATCH] Kill unused sesssion and group values in rocket driver

The process_session() and process_group() values are not really used by the driver.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: containers@lists.osdl.org
Cc: Eric W. Biederman <ebiederm@xmission.com>

drivers/char/rocket.c | 3 ---
drivers/char/rocket_int.h | 2 --
2 files changed, 5 deletions(-)

Index: lx26-20-mm2c/drivers/char/rocket.c

```
=====
--- lx26-20-mm2c.orig/drivers/char/rocket.c 2007-02-28 19:23:00.000000000 -0800
+++ lx26-20-mm2c/drivers/char/rocket.c 2007-02-28 19:24:41.000000000 -0800
@@ -1018,9 +1018,6 @@ static int rp_open(struct tty_struct *tt
/*
 * Info->count is now 1; so it's safe to sleep now.
 */
- info->session = process_session(current);
- info->pgrp = process_group(current);
-
if ((info->flags & ROCKET_INITIALIZED) == 0) {
cp = &info->channel;
sSetRxTrigger(cp, TRIG_1);
```

Index: lx26-20-mm2c/drivers/char/rocket_int.h

```
=====
--- lx26-20-mm2c.orig/drivers/char/rocket_int.h 2007-02-28 19:23:00.000000000 -0800
+++ lx26-20-mm2c/drivers/char/rocket_int.h 2007-02-28 19:24:41.000000000 -0800
@@ -1156,8 +1156,6 @@ struct r_port {
int xmit_head;
int xmit_tail;
int xmit_cnt;
- int session;
- int pgrp;
int cd_status;
int ignore_status_mask;
int read_status_mask;
```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
