
Subject: + use-task_pgrp-task_session-in-copy_process.patch added to -mm tree
Posted by [akpm](#) on Thu, 15 Mar 2007 19:54:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

The patch titled

 Use task_pgrp() task_session() in copy_process()
has been added to the -mm tree. Its filename is
 use-task_pgrp-task_session-in-copy_process.patch

*** Remember to use Documentation/SubmitChecklist when testing your code ***

See <http://www.zip.com.au/~akpm/linux/patches/stuff/added-to-mm.txt> to find out what to do about this

Subject: Use task_pgrp() task_session() in copy_process()
From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Use task_pgrp() and task_session() in copy_process(), and avoid find_pid()
call when attaching the task to its process group and session.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <cld@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: <containers@lists.osdl.org>
Acked-by: Eric W. Biederman <ebiederm@xmission.com>
Signed-off-by: Andrew Morton <akpm@linux-foundation.org>

kernel/fork.c | 9 +++++---
1 file changed, 3 insertions(+), 6 deletions(-)

```
diff -puN kernel/fork.c~use-task_pgrp-task_session-in-copy_process kernel/fork.c
--- a/kernel/fork.c~use-task_pgrp-task_session-in-copy_process
+++ a/kernel/fork.c
@@ -1241,14 +1241,11 @@ static struct task_struct *copy_process(
    tracehook_init_task(p);

    if (thread_group_leader(p)) {
-    pid_t pgid = process_group(current);
-    pid_t sid = process_session(current);
-
-    p->signal->tty = current->signal->tty;
-    p->signal->pgrp = pgid;
+    p->signal->pgrp = process_group(current);
        set_signal_session(p->signal, process_session(current));
-    attach_pid(p, PIDTYPE_PGID, find_pid(pgid));
```

```
- attach_pid(p, PIDTYPE_SID, find_pid(sid));  
+ attach_pid(p, PIDTYPE_PGID, task_pgrp(current));  
+ attach_pid(p, PIDTYPE_SID, task_session(current));  
  
list_add_tail_rcu(&p->tasks, &init_task.tasks);  
__get_cpu_var(process_counts)++;
```

—
Patches currently in -mm which might be from sukadev@us.ibm.com are

```
attach_pid-with-struct-pid-parameter.patch  
statically-initialize-struct-pid-for-swapper.patch  
explicitly-set-pgid-and-sid-of-init-process.patch  
use-struct-pid-parameter-in-copy_process.patch  
remove-the-likelypid-check-in-copy_process.patch  
use-task_pgrp-task_session-in-copy_process.patch  
kill-unused-session-and-group-values-in-rocket-driver.patch  
fix-some-coding-style-errors-in-autofs.patch  
replace-pid_t-in-autofs-with-struct-pid-reference.patch
```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
