

---

Subject: + kill-unused-session-and-group-values-in-rocket-driver.patch added to -mm tree

Posted by [akpm](#) on Thu, 15 Mar 2007 19:54:46 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The patch titled

Kill unused session and group values in rocket driver

has been added to the -mm tree. Its filename is

kill-unused-session-and-group-values-in-rocket-driver.patch

\*\*\* Remember to use Documentation/SubmitChecklist when testing your code \*\*\*

See <http://www.zip.com.au/~akpm/linux/patches/stuff/added-to-mm.txt> to find out what to do about this

-----  
Subject: Kill unused session and group values in rocket driver

From: Sukadev Bhattiprolu <[sukadev@us.ibm.com](mailto:sukadev@us.ibm.com)>

The process\_session() and process\_group() values are not really used by the driver.

Signed-off-by: Sukadev Bhattiprolu <[sukadev@us.ibm.com](mailto:sukadev@us.ibm.com)>

Cc: Cedric Le Goater <[clg@fr.ibm.com](mailto:clg@fr.ibm.com)>

Cc: Dave Hansen <[haveblue@us.ibm.com](mailto:haveblue@us.ibm.com)>

Cc: Serge Hallyn <[serue@us.ibm.com](mailto:serue@us.ibm.com)>

Cc: <[containers@lists.osdl.org](mailto:containers@lists.osdl.org)>

Cc: Eric W. Biederman <[ebiederm@xmission.com](mailto:ebiederm@xmission.com)>

Signed-off-by: Andrew Morton <[akpm@linux-foundation.org](mailto:akpm@linux-foundation.org)>

---

drivers/char/rocket.c | 3 ---

drivers/char/rocket\_int.h | 2 --

2 files changed, 5 deletions(-)

diff -puN drivers/char/rocket.c~kill-unused-session-and-group-values-in-rocket-driver

drivers/char/rocket.c

--- a/drivers/char/rocket.c~kill-unused-session-and-group-values-in-rocket-driver

+++ a/drivers/char/rocket.c

@@ -1014,9 +1014,6 @@ static int rp\_open(struct tty\_struct \*tt

/\*

\* Info->count is now 1; so it's safe to sleep now.

\*/

- info->session = process\_session(current);

- info->pgrp = process\_group(current);

-

if ((info->flags & ROCKET\_INITIALIZED) == 0) {

cp = &info->channel;

```

    sSetRxTrigger(cp, TRIG_1);
diff -puN drivers/char/rocket_int.h~kill-unused-session-and-group-values-in-rocket-driver
drivers/char/rocket_int.h
--- a/drivers/char/rocket_int.h~kill-unused-session-and-group-values-in-rocket-driver
+++ a/drivers/char/rocket_int.h
@@ -1156,8 +1156,6 @@ struct r_port {
    int xmit_head;
    int xmit_tail;
    int xmit_cnt;
- int session;
- int pgrp;
    int cd_status;
    int ignore_status_mask;
    int read_status_mask;

```

Patches currently in -mm which might be from sukadev@us.ibm.com are

```

attach_pid-with-struct-pid-parameter.patch
statically-initialize-struct-pid-for-swapper.patch
explicitly-set-pgid-and-sid-of-init-process.patch
use-struct-pid-parameter-in-copy_process.patch
remove-the-likelypid-check-in-copy_process.patch
use-task_pgrp-task_session-in-copy_process.patch
kill-unused-session-and-group-values-in-rocket-driver.patch
fix-some-coding-style-errors-in-autofs.patch
replace-pid_t-in-autofs-with-struct-pid-reference.patch

```

---

Containers mailing list  
Containers@lists.osdl.org  
<https://lists.osdl.org/mailman/listinfo/containers>

---